



XLstep S

Low weight, simple handling and a good price/performance ratio with high-value equipment.

Product description

- Low weight, simple handling and a good price/performance ratio with high-value equipment.
- Stand without fatigue on deep treads.
- Large platform that allows personnel to stand safely and comfortably even when working for extended periods.
- Treads with a depth of 80 mm for fatigue-free standing.
- Abrasion-resistant, anodised stiles.
- Platform made from extruded aluminium (300 mm x 250 mm) for safe and comfortable standing even when working for longer periods of time.
- Spacious aluminium storage tray for material and tools.
- High-strength Perlon belts prevent splay, fitted on all models of 4 rungs or more.
- Triple-riveted connection between treads and stiles.
- Non-slip plastic end caps.
- Treads and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating anodised	Connection Stile-Rung riveted	Load capacity max. 150 kg	Material Aluminium	Pitch rung/tread 250 mm
Platform length 250 mm	Platform width 300 mm	Standards EN 131 professional	Stile depth 42 mm	Tray Aluminium



Tread depth

80 mm

Type rung/tread

serrated

Warranty

10 years

Product variants

SKU 41223	SKU 41224	SKU 41225
Base 0,74 m × 0,49 m	Anti splay Belt strap	Anti splay Belt strap
Number of rungs, incl. platform 3	Base 0,91 m × 0,52 m	Base 1,08 m × 0,55 m
Overall base width 0.49 m	Number of rungs, incl. platform 4	Number of rungs, incl. platform 5
Overall length 1.56 m	Overall base width 0.52 m	Overall base width 0.55 m
Platform height 0.74 m	Overall length 1.83 m	Overall length 2.1 m
Stile depth 42 mm	Platform height 0.99 m	Platform height 1.24 m
Stile depth steps/back stay 42mm / 42mm	Stile depth 42 mm	Stile depth 42 mm
Transport dimensions approx. 1.560 mm × approx. 490 mm × approx. 155 mm	Stile depth steps/back stay 42mm / 42mm	Stile depth steps/back stay 42mm / 42mm
Vertical ladder height 1.42 m	Transport dimensions approx. 1.830 mm × approx. 520 mm × approx. 155 mm	Transport dimensions approx. 2.100 mm × approx. 550 mm × approx. 155 mm
Weight 6 kg	Vertical ladder height 1.67 m	Vertical ladder height 1.92 m
Working height	Weight	Weight



2.75 m	6.9 kg	7.7 kg
	Working height 3 m	Working height 3.25 m
SKU 41226	SKU 41227	SKU 41228
Anti splay Belt strap	Anti splay Belt strap	Anti splay Belt strap
Base 1,25 m × 0,57 m	Base 1,42 m × 0,61 m	Base 1,59 m × 0,63 m
Number of rungs, incl. platform 6	Number of rungs, incl. platform 7	Number of rungs, incl. platform 8
Overall base width 0.57 m	Overall base width 0.61 m	Overall base width 0.63 m
Overall length 2.37 m	Overall length 2.64 m	Overall length 2.91 m
Platform height 1.49 m	Platform height 1.74 m	Platform height 1.99 m
Stile depth 48 mm	Stile depth 48 mm	Stile depth 48 mm
Stile depth steps/back stay 48mm / 42mm	Stile depth steps/back stay 48mm / 42mm	Stile depth steps/back stay 48mm / 42mm
Transport dimensions approx. 2.370 mm × approx. 570 mm × approx. 155 mm	Transport dimensions approx. 2.640 mm × approx. 610 mm × approx. 155 mm	Transport dimensions approx. 2.910 mm × approx. 630 mm × approx. 155 mm
Vertical ladder height 2.17 m	Vertical ladder height 2.42 m	Vertical ladder height 2.67 m
Weight 9.1 kg	Weight 10.2 kg	Weight 11.7 kg



Working height 3.5 m	Working height 3.75 m	Working height 4 m
SKU 41230		
Anti splay Belt strap		
Base 1,93 m × 0,69 m		
Number of rungs, incl. platform 10		
Overall base width 0.69 m		
Overall length 3.45 m		
Platform height 2.49 m		
Stile depth 48 mm		
Stile depth steps/back stay 48mm / 42mm		
Transport dimensions approx. 3.450 mm × approx. 690 mm × approx. 155 mm		
Vertical ladder height 3.17 m		
Weight 14.1 kg		
Working height		



4.5 m