



# Scana S

High degree of comfort while working due to abrasion-resistant, anodised stiles and large storage tray.

## Product description

- High degree of comfort while working due to abrasion-resistant, anodised stiles and large storage tray.
- Large platform with anti-slip ribbing.
- Tread depth 80 mm.
- Abrasion-resistant, anodised stiles.
- Practical tray with plenty of space for tools and small items.
- High-strength Perlon belts prevent splay from 6 rungs.
- The extruded aluminium sections give the platform optimum stability.
- Two extruded section bridge raisers.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Coating <b>anodised</b>	Connection Stile-Rung <b>riveted</b>	Load capacity <b>max. 150 kg</b>	Material <b>Aluminium</b>	Pitch rung/tread <b>216 mm</b>
Platform length <b>250 mm</b>	Platform width <b>250 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>40 mm</b>	Stile depth <b>40 mm</b>
Stile depth steps/back stay <b>40mm / 40mm</b>	Tray <b>Plastic</b>	Tread depth <b>80 mm</b>	Type rung/tread <b>serrated</b>	Warranty <b>10 years</b>

## Product variants



SKU <b>44153</b>	SKU <b>44154</b>	SKU <b>44155</b>
Base <b>0,67 m × 0,41 m</b>	Base <b>0,82 m × 0,43 m</b>	Base <b>0,96 m × 0,46 m</b>
Number of rungs, incl. platform <b>3</b>	Number of rungs, incl. platform <b>4</b>	Number of rungs, incl. platform <b>5</b>
Overall base width <b>0.41 m</b>	Overall base width <b>0.43 m</b>	Overall base width <b>0.46 m</b>
Overall length <b>1.36 m</b>	Overall length <b>1.59 m</b>	Overall length <b>1.82 m</b>
Platform height <b>0.59 m</b>	Platform height <b>0.81 m</b>	Platform height <b>1.03 m</b>
Transport dimensions <b>1.370 mm × 410 mm × 110 mm</b>	Transport dimensions <b>1.600 mm × 440 mm × 110 mm</b>	Transport dimensions <b>1.830 mm × 460 mm × 110 mm</b>
Vertical ladder height <b>1.2 m</b>	Vertical ladder height <b>1.42 m</b>	Vertical ladder height <b>1.64 m</b>
Weight <b>3.7 kg</b>	Weight <b>4.4 kg</b>	Weight <b>5.1 kg</b>
Working height <b>2.6 m</b>	Working height <b>2.8 m</b>	Working height <b>3 m</b>
SKU <b>44156</b>	SKU <b>44157</b>	SKU <b>44158</b>
Anti splay <b>Belt strap</b>	Anti splay <b>Belt strap</b>	Anti splay <b>Belt strap</b>
Base <b>1,1 m × 0,48 m</b>	Base <b>1,25 m × 0,51 m</b>	Base <b>1,7 m × 0,53 m</b>
Number of rungs, incl. platform <b>6</b>	Number of rungs, incl. platform <b>7</b>	Number of rungs, incl. platform <b>8</b>



Overall base width <b>0.48 m</b>	Overall base width <b>0.51 m</b>	Overall base width <b>0.53 m</b>
Overall length <b>2.05 m</b>	Overall length <b>2.29 m</b>	Overall length <b>2.52 m</b>
Platform height <b>1.24 m</b>	Platform height <b>1.47 m</b>	Platform height <b>1.7 m</b>
Transport dimensions <b>2.060 mm × 490 mm × 110 mm</b>	Transport dimensions <b>2.290 mm × 510 mm × 110 mm</b>	Transport dimensions <b>2.520 mm × 530 mm × 110 mm</b>
Vertical ladder height <b>1.85 m</b>	Vertical ladder height <b>2.08 m</b>	Vertical ladder height <b>2.31 m</b>
Weight <b>5.9 kg</b>	Weight <b>6.6 kg</b>	Weight <b>8 kg</b>
Working height <b>3.25 m</b>	Working height <b>3.5 m</b>	Working height <b>3.7 m</b>