




# Saferstep B

The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.

## Product description

- The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.
- Maximum working heights thanks to 280mm high access.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Anti splay <b>Belt strap</b>	Coating <b>anodised</b>	Connection Stile-Rung <b>flanged</b>	Load capacity <b>max. 150 kg</b>	Material <b>Aluminium</b>
Pitch rung/tread <b>265 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>68 mm</b>	Tread depth <b>80 mm</b>	Type rung/tread <b>Safer Step</b>
Warranty <b>10 years</b>				

## Product variants



SKU <b>41303</b>	SKU <b>41304</b>	SKU <b>41305</b>
Base <b>0,8 m × 0,44 m</b>	Base <b>0,99 m × 0,47 m</b>	Base <b>1,18 m × 0,5 m</b>
Number of treads <b>2 × 3</b>	Number of treads <b>2 × 4</b>	Number of treads <b>2 × 5</b>
Overall base width <b>0.44 m</b>	Overall base width <b>0.47 m</b>	Overall base width <b>0.5 m</b>
Overall length <b>0.88 m</b>	Overall length <b>1.15 m</b>	Overall length <b>1.42 m</b>
Transport dimensions <b>875 mm × 445 mm × 230 mm</b>	Transport dimensions <b>1.153 mm × 475 mm × 230 mm</b>	Transport dimensions <b>1.425 mm × 505 mm × 230 mm</b>
Vertical ladder height <b>0.8 m</b>	Vertical ladder height <b>1.06 m</b>	Vertical ladder height <b>1.32 m</b>
Weight <b>4.6 kg</b>	Weight <b>6.1 kg</b>	Weight <b>7.6 kg</b>
Working height <b>2.3 m</b>	Working height <b>2.55 m</b>	Working height <b>2.8 m</b>
SKU <b>41306</b>	SKU <b>41307</b>	SKU <b>41308</b>
Base <b>1,38 m × 0,53 m</b>	Base <b>1,58 m × 0,56 m</b>	Base <b>1,77 m × 0,59 m</b>
Number of treads <b>2 × 6</b>	Number of treads <b>2 × 7</b>	Number of treads <b>2 × 8</b>
Overall base width <b>0.53 m</b>	Overall base width <b>0.56 m</b>	Overall base width <b>0.59 m</b>
Overall length <b>1.7 m</b>	Overall length <b>1.98 m</b>	Overall length <b>2.27 m</b>



Transport dimensions <b>1.705 mm × 535 mm × 230 mm</b>	Transport dimensions <b>1.985 mm × 565 mm × 230 mm</b>	Transport dimensions <b>2.275 mm × 595 mm × 230 mm</b>
Vertical ladder height <b>1.58 m</b>	Vertical ladder height <b>1.84 m</b>	Vertical ladder height <b>2.1 m</b>
Weight <b>9.3 kg</b>	Weight <b>10.9 kg</b>	Weight <b>12.7 kg</b>
Working height <b>3.05 m</b>	Working height <b>3.3 m</b>	Working height <b>3.6 m</b>
SKU <b>41310</b>	SKU <b>41312</b>	SKU <b>41314</b>
Base <b>2,16 m × 0,65 m</b>	Base <b>2,55 m × 0,71 m</b>	Base <b>2,95 m × 0,77 m</b>
Number of treads <b>2 × 10</b>	Number of treads <b>2 × 12</b>	Number of treads <b>2 × 14</b>
Overall base width <b>0.65 m</b>	Overall base width <b>0.71 m</b>	Overall base width <b>0.77 m</b>
Overall length <b>2.83 m</b>	Overall length <b>3.39 m</b>	Overall length <b>3.95 m</b>
Transport dimensions <b>2.835 mm × 655 mm × 230 mm</b>	Transport dimensions <b>3.390 mm × 715 mm × 230 mm</b>	Transport dimensions <b>3.950 mm × 775 mm × 230 mm</b>
Vertical ladder height <b>2.62 m</b>	Vertical ladder height <b>3.15 m</b>	Vertical ladder height <b>3.67 m</b>
Weight <b>16.4 kg</b>	Weight <b>20.3 kg</b>	Weight <b>24.4 kg</b>
Working height <b>4.15 m</b>	Working height <b>4.65 m</b>	Working height <b>5.2 m</b>
SKU		



**41316**

Base

**3,34 m × 0,83 m**

Number of treads

**2 × 16**

Overall base width

**0.83 m**

Overall length

**4.51 m**

Transport dimensions

**4.510 mm × 830 mm × 230 mm**

Vertical ladder height

**4.21 m**

Weight

**28.8 kg**

Working height

**5.7 m**