



Comfortstep B

Shin protection during ascent and descent and attractive design ensure high comfort when working and a flexible range of applications.

Product description

- Shin protection during ascent and descent and attractive design ensure high comfort when working and a flexible range of applications.
- Deep treads with padded front edge for standing comfort.
- 80 mm deep treads with padded front edges.
- Abrasion-resistant, anodised stiles.
- High-strength perlon belts prevent splay.
- · Treads with plastic-cushioned front edges.
- Non-slip plastic end caps.
- Treads and stiles made from extruded aluminium sections.
- Screwed connection between treads and stile.







Hints and special features

Maximum comfort due to padded treads. Complies with EN 131 Professional.

Product features

Anti splay	Coating	Connection Stile-Rung	Load capacity	Material
Belt strap	anodised	bolted	max. 150 kg	Aluminium
Pitch rung/tread	Standards	Tread depth	Type rung/tread	Warranty
250 mm	EN 131 professional	80 mm	padding on front tread edges	10 years
	professional		ireau euges	

Product variants

82362 Weilheim





SKU 41432	SKU 41433	SKU 41434
Base 0,74 m × 0,44 m	Base 0,95 m × 0,47 m	Base 1,15 m × 0,5 m
Number of treads 2 × 3	Number of treads 2 × 4	Number of treads 2 × 5
Overall base width 0.44 m	Overall base width 0.47 m	Overall base width 0.5 m
Overall length 0.84 m	Overall length 1.11 m	Overall length 1.38 m
Stile depth 42 mm	Stile depth 42 mm	Stile depth 42 mm
Transport dimensions 840 mm × 445 mm × 174 mm	Transport dimensions 1.110 mm × 470 mm × 174 mm	Transport dimensions 1.380 mm × 500 mm × 174 mm
Vertical ladder height 0.75 m	Vertical ladder height 1 m	Vertical ladder height 1.25 m
Weight 4.4 kg	Weight 5.8 kg	Weight 7.3 kg
Working height 2.25 m	Working height 2.5 m	Working height 2.75 m
SKU 41435	SKU 41436	SKU 41437
Base 1,35 m × 0,53 m	Base 1,55 m × 0,56 m	Base 1,75 m × 0,59 m
Number of treads 2 × 6	Number of treads 2 × 7	Number of treads 2 × 8
Overall base width 0.53 m	Overall base width 0.56 m	Overall base width 0.59 m





Overall length 1.65 m	Overall length 1.92 m	Overall length 2.18 m
Stile depth 42 mm	Stile depth 42 mm	Stile depth 48 mm
Transport dimensions 1.650 mm × 530 mm × 174 mm	Transport dimensions 1.920 mm × 560 mm × 174 mm	Transport dimensions 2.185 mm × 590 mm × 174 mm
Vertical ladder height 1.5 m	Vertical ladder height 1.75 m	Vertical ladder height 2 m
Weight 8.8 kg	Weight 10.3 kg	Weight 12.2 kg
Working height 3 m	Working height 3.25 m	Working height 3.5 m
SKU 41438	SKU 41430	
Base 2,16 m × 0,65 m	Base 2,36 m × 0,68 m	
Number of treads 2 × 10	Number of treads 2 x 11	
Overall base width 0.65 m	Overall base width 0.68 m	
Overall length 2.72 m	Overall length 2.99 m	
Stile depth 48 mm	Stile depth 48 mm	
Transport dimensions 2.725 mm × 650 mm × 174 mm	Transport dimensions 3.000 mm × 680 mm × 174 mm	
Vertical ladder height	Vertical ladder height	





2.5 m	2.75 m
Weight 15.8 kg	Weight 17.6 kg
Working height 4 m	Working height 4.25 m