



Scana B

Flexible working and pleasant to handle due to the anodised stiles.

Product description

- Flexible working and pleasant to handle due to the anodised stiles.
- Tread depth 80 mm.
- Abrasion-resistant, anodised stiles.
- High-strength perlon belts prevent splay.

Hints and special features

Complies with EN 131 Professional.



Product features

Anti splay Belt strap	Coating anodised	Connection Stile-Rung riveted	Load capacity max. 150 kg	Material Aluminium
Pitch rung/tread 216 mm	Standards EN 131 professional	Stile depth 40 mm	Tread depth 80 mm	Type rung/tread serrated
Warranty 10 years				

Product variants

SKU 44203	SKU 44204	SKU 44205
Base	Base	Base



0,59 m × 0,43 m	0,76 m × 0,45 m	0,91 m × 0,48 m
Number of treads 2 × 3	Number of treads 2 × 4	Number of treads 2 × 5
Overall base width 0.43 m	Overall base width 0.45 m	Overall base width 0.48 m
Overall length 0.71 m	Overall length 0.94 m	Overall length 1.17 m
Transport dimensions 710 mm × 430 mm × 160 mm	Transport dimensions 940 mm × 460 mm × 160 mm	Transport dimensions 1.170 mm × 480 mm × 160 mm
Vertical ladder height 0.66 m	Vertical ladder height 0.87 m	Vertical ladder height 1.09 m
Weight 3 kg	Weight 3.8 kg	Weight 4.8 kg
Working height 2.2 m	Working height 2.45 m	Working height 2.65 m
SKU 44206	SKU 44207	
Base 1,1 m × 0,5 m	Base 1,28 m × 0,52 m	
Number of treads 2 × 6	Number of treads 2 × 7	
Overall base width 0.5 m	Overall base width 0.52 m	
Overall length 1.4 m	Overall length 1.66 m	
Transport dimensions 1.400 mm × 500 mm × 160 mm	Transport dimensions 1.630 mm × 530 mm × 160 mm	



Vertical ladder height 1.3 m	Vertical ladder height 1.52 m
Weight 5.8 kg	Weight 6.8 kg
Working height 2.85 m	Working height 3.1 m