



Coni B

Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.

Product description

- Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.
- Sturdy aluminium alloy rungs (30 x 30 mm) with non-slip serrated surface.
- Sturdy, solidly screwed steel hinges
- Two high-strength Perlon belts, secured without twisting to the rung, prevent splay.
- High strength, non-twist rung/stile connections.
- Additional stabilisation by bracing on the bottom rung.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Step ladder for maximum working heights of up to 6.70 m.

Complies with EN 131 Professional.

Product features

Anti splay Belt strap	Coating natural	Connection Stile-Rung flanged	Load capacity max. 150 kg	Material Aluminium
Pitch rung/tread 265 mm	Standards EN 131 professional	Tread depth 30 mm	Type rung/tread serrated	Warranty 10 years

Product variants



SKU 40274	SKU 40275	SKU 40311
Base 0,78 m × 0,48 m	Base 0,93 m × 0,51 m	Base 1,07 m × 0,54 m
Number of rungs 2 × 4	Number of rungs 2 × 5	Number of rungs 2 × 6
Overall base width 0.48 m	Overall base width 0.51 m	Overall base width 0.54 m
Overall length 1.25 m	Overall length 1.53 m	Overall length 1.81 m
Stile depth 50 mm	Stile depth 58 mm	Stile depth 58 mm
Transport dimensions 1.250 mm × 480 mm × 170 mm	Transport dimensions 1.530 mm × 510 mm × 170 mm	Transport dimensions 1.810 mm × approx. 540 mm × approx. 170 mm
Vertical ladder height 1.2 m	Vertical ladder height 1.46 m	Vertical ladder height 1.73 m
Weight 4.4 kg	Weight 5.8 kg	Weight 6.8 kg
Working height 2.5 m	Working height 2.75 m	Working height 3 m
SKU 40277	SKU 40312	SKU 40313
Base 1,22 m × 0,57 m	Base 1,36 m × 0,6 m	Base 1,65 m × 0,66 m
Number of rungs 2 × 7	Number of rungs 2 × 8	Number of rungs 2 × 10
Overall base width	Overall base width	Overall base width



0.57 m	0.6 m	0.66 m
Overall length 2.09 m	Overall length 2.36 m	Overall length 2.92 m
Stile depth 58 mm	Stile depth 58 mm	Stile depth 58 mm
Transport dimensions approx. 2.090 mm × 570 mm × approx. 170 mm	Transport dimensions approx. 2.370 mm × approx. 600 mm × approx. 170 mm	Transport dimensions approx. 2.930 mm × approx. 660 mm × approx. 170 mm
Vertical ladder height 1.99 m	Vertical ladder height 2.3 m	Vertical ladder height 2.83 m
Weight 7.3 kg	Weight 9 kg	Weight 11.1 kg
Working height 3.25 m	Working height 3.55 m	Working height 4.05 m
SKU 40314	SKU 40315	SKU 40316
Base 1,94 m × 0,72 m	Base 2,24 m × 0,78 m	Base 2,54 m × 0,84 m
Number of rungs 2 × 12	Number of rungs 2 × 14	Number of rungs 2 × 16
Overall base width 0.72 m	Overall base width 0.78 m	Overall base width 0.84 m
Overall length 3.48 m	Overall length 4.04 m	Overall length 4.61 m
Stile depth 58 mm	Stile depth 62 mm	Stile depth 68 mm
Transport dimensions approx. 3.490 mm × approx. 720 mm × approx. 170 mm	Transport dimensions approx. 4.050 mm × approx. 780 mm × approx. 175 mm	Transport dimensions approx. 4.610 mm × approx. 840 mm × approx. 190 mm



Vertical ladder height 3.37 m	Vertical ladder height 3.91 m	Vertical ladder height 4.45 m
Weight 13.3 kg	Weight 17.2 kg	Weight 21.2 kg
Working height 4.6 m	Working height 5.1 m	Working height 5.65 m
SKU 40320	SKU 40317	
Base 2,84 m × 0,9 m	Base 3,13 m × 0,96 m	
Number of rungs 2 × 18	Number of rungs 2 × 20	
Overall base width 0.9 m	Overall base width 0.96 m	
Overall length 5.17 m	Overall length 5.73 m	
Stile depth 73 mm	Stile depth 73 mm	
Transport dimensions approx. 5.170 mm × approx. 900 mm × approx. 200 mm	Transport dimensions approx. 5.730 mm × approx. 960 mm × approx. 200 mm	
Vertical ladder height 5 m	Vertical ladder height 5.54 m	
Weight 25.6 kg	Weight 29.8 kg	
Working height 6.15 m	Working height 6.7 m	