



EFA B

For flexible applications in electrical or chemical environments and for working under voltage.

Product description


- For flexible applications in electrical or chemical environments and for working under voltage.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Stiles and rungs (30 x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- High-strength perlon belts prevent splay.
- Replaceable 2-component plastic end caps ensure positioning without the risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Complies with EN 131 Professional.

Product features





Anti splay Belt strap	Load capacity max. 150 kg	Material Glass-fibre reinforced plastic	Pitch rung/tread 265 mm	Standards EN 131 professional
Stile depth 58 mm	Tread depth 30 mm	Type rung/tread serrated	Warranty 10 years	

Product variants

SKU 41261	SKU 41256	SKU 41257
Base 1,08 m × 0,48 m	Base 1,31 m × 0,54 m	Base 1,66 m × 0,6 m
Number of rungs 2 × 4	Number of rungs 2 × 6	Number of rungs 2 × 8
Overall base width 0.48 m	Overall base width 0.54 m	Overall base width 0.6 m
Overall length 1.32 m	Overall length 1.88 m	Overall length 2.44 m
Transport dimensions 1.350 mm × 480 mm × 162 mm	Transport dimensions 1.900 mm × 540 mm × 162 mm	Transport dimensions 2.460 mm × 600 mm × 162 mm
Vertical ladder height 1.27 m	Vertical ladder height 1.82 m	Vertical ladder height 2.35 m
Weight 7.5 kg	Weight 10.5 kg	Weight 13.8 kg
Working height 2.6 m	Working height 3.1 m	Working height 3.65 m



SKU	SKU
41258	41260
Base	Base
2,01 m × 0,66 m	2,7 m × 0,78 m
Number of rungs	Number of rungs
2 × 10	2 × 14
Overall base width	Overall base width
0.65 m	0.77 m
Overall length	Overall length
3 m	4.12 m
Transport dimensions	Transport dimensions
3.000 mm × 660 mm × 160 mm	4.150 mm × 770 mm × 160 mm
Vertical ladder height	Vertical ladder height
2.89 m	3.95 m
Weight	Weight
17 kg	24.6 kg
Working height	Working height
4.15 m	5.2 m