



EFAmix B

The ideal, particularly lightweight solution for work in electrical and chemical environments.

Product description

- The ideal, particularly lightweight solution for work in electrical and chemical environments.
- High level of protection provided for working on electrical installations thanks to insulated stiles made from glass-fibre-reinforced plastic.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Stand safely on 60 mm deep rungs made from non-slip aluminium alloy.
- High-strength perlon belts prevent splay.
- High strength, non-twist rung/stile connections.
- Strong steel hinge.
- Replaceable 2-component plastic end caps ensure positioning without the risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay Belt strap	Connection Stile-Rung flanged	Load capacity max. 150 kg	Material Aluminium / plastic	Pitch rung/tread 265 mm
Standards EN 131 professional	Stile depth 58 mm	Tread depth 60 mm	Type rung/tread serrated	Warranty 10 years

Product variants



SKU 41165	SKU 41166	SKU 41167
Base 0,96 m × 0,48 m	Base 1,13 m × 0,51 m	Base 1,31 m × 0,54 m
Number of rungs 2 × 4	Number of rungs 2 × 5	Number of rungs 2 × 6
Overall base width 0.47 m	Overall base width 0.5 m	Overall base width 0.53 m
Overall length 1.34 m	Overall length 1.62 m	Overall length 1.9 m
Transport dimensions 1.344 mm × 480 mm × 162 mm	Transport dimensions 1.625 mm × 510 mm × 162 mm	Transport dimensions 1.904 mm × 540 mm × 162 mm
Vertical ladder height 1.29 m	Vertical ladder height 1.55 m	Vertical ladder height 1.82 m
Weight 7.8 kg	Weight 9.6 kg	Weight 11.4 kg
Working height 2.6 m	Working height 2.85 m	Working height 3.1 m
SKU 41168	SKU 41169	SKU 41170
Base 1,81 m × 0,6 m	Base 2,17 m × 0,66 m	Base 2,55 m × 0,72 m
Number of rungs 2 × 8	Number of rungs 2 × 10	Number of rungs 2 × 12
Overall base width 0.59 m	Overall base width 0.65 m	Overall base width 0.71 m
Overall length 2.46 m	Overall length 3.02 m	Overall length 3.58 m



Transport dimensions 2.464 mm × 600 mm × 162 mm	Transport dimensions 3.024 mm × 660 mm × 162 mm	Transport dimensions 3.584 mm × 720 mm × 162 mm
Vertical ladder height 2.33 m	Vertical ladder height 2.86 m	Vertical ladder height 3.38 m
Weight 14.8 kg	Weight 18.8 kg	Weight 22.5 kg
Working height 3.65 m	Working height 4.15 m	Working height 4.7 m