



Skymaster DX

The basic version offers high functionality and flexibility and an excellent price/performance ratio.


Product description

- The basic version offers high functionality and flexibility and an excellent price/performance ratio.
- Upper ladder can also be used separately as single ladders for Order Nos. 44837-44840.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Strong Perlon straps.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.
- Cannot be used on stairs.



Hints and special features

Complies with EN 131 Professional.



Product features

| | | | | |
|---|---|-------------------------------------|------------------------------|-----------------------------------|
| Coating natural | Connection Stile-Rung flanged | Load capacity max. 150 kg | Material Aluminium | Pitch rung/tread 265 mm |
| Standards EN 131 professional | Tread depth 38 mm | Type rung/tread serrated | Warranty 10 years | |

Product variants

| | | |
|---------------------|---------------------|---------------------|
| SKU 44837 | SKU 44838 | SKU 44839 |
|---------------------|---------------------|---------------------|



| | | |
|---|---|--|
| Ladder length as 3-part single ladder 4.4 m | Ladder length as 3-part single ladder 5.25 m | Ladder length as 3-part single ladder 6.1 m |
| Length as 2-part single ladder and as stepladder with push-on section 3.25 m | Length as 2-part single ladder and as stepladder with push-on section 3.85 m | Length as 2-part single ladder and as stepladder with push-on section 4.4 m |
| Number of rungs 3 x 7 | Number of rungs 3 x 8 | Number of rungs 3 x 9 |
| Overall length, retracted 2.14 m | Overall length, retracted 2.42 m | Overall length, retracted 2.7 m |
| Stile depth 58 mm | Stile depth 68 mm | Stile depth 73 mm |
| Transport dimensions 2.130 mm x 500 mm x 170 mm | Transport dimensions 2.410 mm x 500 mm x 170 mm | Transport dimensions 2.690 mm x 500 mm x 190 mm |
| Weight 13.8 kg | Weight 16.3 kg | Weight 18 kg |
| Wide crosspiece 0.8 m | Wide crosspiece 0.9 m | Wide crosspiece 1 m |
| Working height as 3-part single ladder 5.2 m | Working height as 3-part single ladder 6 m | Working height as 3-part single ladder 6.85 m |
| SKU 44840 | SKU 44841 | SKU 44842 |
| Ladder length as 3-part single ladder 6.65 m | Ladder length as 3-part single ladder 7.2 m | Ladder length as 3-part single ladder 8.3 m |
| Length as 2-part single ladder and as stepladder with push-on section 4.65 m | Length as 2-part single ladder and as stepladder with push-on section 5.25 m | Length as 2-part single ladder and as stepladder with push-on section 5.8 m |
| Number of rungs 3 x 10 | Number of rungs 3 x 11 | Number of rungs 3 x 12 |
| Overall length, retracted | Overall length, retracted | Overall length, retracted |



| | | |
|---|--|--|
| 2.98 m | 3.26 m | 3.54 m |
| Stile depth | Stile depth | Stile depth |
| 73 mm | 85 mm | 85 mm |
| Transport dimensions | Transport dimensions | Transport dimensions |
| 2.970 mm × 500 mm × 190 mm | 3.270 mm × 500 mm × 200 mm | 3.550 mm × 500 mm × 220 mm |
| Weight | Weight | Weight |
| 20.5 kg | 22.3 kg | 25.9 kg |
| Wide crosspiece | Wide crosspiece | Wide crosspiece |
| 1.1 m | 1.1 m | 1.2 m |
| Working height as 3-part single ladder | Working height as 3-part single ladder | Working height as 3-part single ladder |
| 7.35 m | 7.9 m | 9 m |
| SKU | | |
| 44844 | | |
| Ladder length as 3-part single ladder | | |
| 9.45 m | | |
| Length as 2-part single ladder and as stepladder with push-on section | | |
| 6.654 m | | |
| Number of rungs | | |
| 3 × 14 | | |
| Overall length, retracted | | |
| 4.1 m | | |
| Stile depth | | |
| 98 mm | | |
| Transport dimensions | | |
| 4.110 mm × 500 mm × 220 mm | | |
| Weight | | |
| 31.5 kg | | |



Wide crosspiece

1.2 m

Working height as 3-part single ladder

10.05 m