



# Skymaster DX

The basic version offers high functionality and flexibility and an excellent price/performance ratio.

## Product description

- The basic version offers high functionality and flexibility and an excellent price/performance ratio.
- Upper ladder can also be used separately as single ladders for Order Nos. 44837-44840.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Strong Perlon straps.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.
- Cannot be used on stairs.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Coating <b>natural</b>	Connection Stile-Rung <b>flanged</b>	Load capacity <b>max. 150 kg</b>	Material <b>Aluminium</b>	Pitch rung/tread <b>265 mm</b>
Standards <b>EN 131 professional</b>	Tread depth <b>38 mm</b>	Type rung/tread <b>serrated</b>	Warranty <b>10 years</b>	



## Product variants

SKU <b>44837</b>	SKU <b>44838</b>	SKU <b>44839</b>
Ladder length as 3-part single ladder <b>4.4 m</b>	Ladder length as 3-part single ladder <b>5.25 m</b>	Ladder length as 3-part single ladder <b>6.1 m</b>
Length as 2-part single ladder and as stepladder with push-on section <b>3.25 m</b>	Length as 2-part single ladder and as stepladder with push-on section <b>3.85 m</b>	Length as 2-part single ladder and as stepladder with push-on section <b>4.4 m</b>
Number of rungs <b>3 × 7</b>	Number of rungs <b>3 × 8</b>	Number of rungs <b>3 × 9</b>
Overall length, retracted <b>2.14 m</b>	Overall length, retracted <b>2.42 m</b>	Overall length, retracted <b>2.7 m</b>
Stile depth <b>58 mm</b>	Stile depth <b>68 mm</b>	Stile depth <b>73 mm</b>
Transport dimensions <b>2.130 mm × 500 mm × 170 mm</b>	Transport dimensions <b>2.410 mm × 500 mm × 170 mm</b>	Transport dimensions <b>2.690 mm × 500 mm × 190 mm</b>
Weight <b>13.8 kg</b>	Weight <b>16.3 kg</b>	Weight <b>18 kg</b>
Wide crosspiece <b>0.8 m</b>	Wide crosspiece <b>0.9 m</b>	Wide crosspiece <b>1 m</b>
Working height as 3-part single ladder <b>5.2 m</b>	Working height as 3-part single ladder <b>6 m</b>	Working height as 3-part single ladder <b>6.85 m</b>
SKU <b>44840</b>	SKU <b>44841</b>	SKU <b>44842</b>
Ladder length as 3-part single ladder	Ladder length as 3-part single ladder	Ladder length as 3-part single ladder



<b>6.65 m</b>	<b>7.2 m</b>	<b>8.3 m</b>
Length as 2-part single ladder and as stepladder with push-on section	Length as 2-part single ladder and as stepladder with push-on section	Length as 2-part single ladder and as stepladder with push-on section
<b>4.65 m</b>	<b>5.25 m</b>	<b>5.8 m</b>
Number of rungs	Number of rungs	Number of rungs
<b>3 × 10</b>	<b>3 × 11</b>	<b>3 × 12</b>
Overall length, retracted	Overall length, retracted	Overall length, retracted
<b>2.98 m</b>	<b>3.26 m</b>	<b>3.54 m</b>
Stile depth	Stile depth	Stile depth
<b>73 mm</b>	<b>85 mm</b>	<b>85 mm</b>
Transport dimensions	Transport dimensions	Transport dimensions
<b>2.970 mm × 500 mm × 190 mm</b>	<b>3.270 mm × 500 mm × 200 mm</b>	<b>3.550 mm × 500 mm × 220 mm</b>
Weight	Weight	Weight
<b>20.5 kg</b>	<b>22.3 kg</b>	<b>25.9 kg</b>
Wide crosspiece	Wide crosspiece	Wide crosspiece
<b>1.1 m</b>	<b>1.1 m</b>	<b>1.2 m</b>
Working height as 3-part single ladder	Working height as 3-part single ladder	Working height as 3-part single ladder
<b>7.35 m</b>	<b>7.9 m</b>	<b>9 m</b>
SKU		
<b>44844</b>		
Ladder length as 3-part single ladder		
<b>9.45 m</b>		
Length as 2-part single ladder and as stepladder with push-on section		
<b>6.654 m</b>		
Number of rungs		



**3 × 14**

Overall length, retracted

**4.1 m**

Stile depth

**98 mm**

Transport dimensions

**4.110 mm × 500 mm × 220 mm**

Weight

**31.5 kg**

Wide crosspiece

**1.2 m**

Working height as 3-part single ladder

**10.05 m**