



Varioflex B

Special ladder that ensures safe standing even when working on uneven ground, on steps and overhangs.

Product description

- Special ladder that ensures safe standing even when working on uneven ground, on steps and overhangs.
- Continuous adjustment to the millimetre. Each individual stile of the ladder locks securely by the turn of a handle.
- Stile dimensions: 60 x 24 mm.
- Rungs and stiles made from extruded aluminium sections.
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Ideal for applications in difficult terrain.
 Complies with EN 131 Professional.



Product features

Additional adjustment range on ladder section 0.4 m	Coating natural	Connection Stile-Rung flanged	Load capacity max. 150 kg	Material Aluminium
Pitch rung/tread 265 mm	Tread depth 30 mm	Type rung/tread serrated	Warranty 10 years	

Product variants

SKU 41936	SKU 41938
---------------------	---------------------



Additional adjustment range on support section 1.3 m	Additional adjustment range on support section 1.85 m
Length excluding extension 1.8 m	Length excluding extension 2.35 m
Number of rungs 2 x 6	Number of rungs 2 x 8
Transport dimensions 1.850 mm x 600 mm x 140 mm	Transport dimensions 2.410 mm x 650 mm x 140 mm
Weight 12.5 kg	Weight 15.5 kg
Working height 3 m	Working height 3.55 m