




Multi-section fixed ladder systems, anodised aluminium

Multi-section access solution with crossover platform for buildings and machinery.

Product description

- For permanent installation to BGV D 36 and DIN 18 799-1, DIN 14 094-1 and EN ISO 14 122-4.
- With back guards.
- Ladder width: 520 mm.
- Wall brackets with various wall distances up to 600 mm can be selected.
- The distance between the wall brackets is max. 2.00 m. But each ladder section must be mounted with at least 2 wall brackets.
- Safety barriers, access protection and platforms can be selected to suit individual requirements.
- On request, we can also produce fixed-ladders that differ from the standard specifications.



Hints and special features

Dowels and screws/bolts for wall mounting are not included in the scope of delivery.

The prices for double-section systems listed below are calculated as follows: Wall bracket in the form of a U-bar, 200 mm rigid, straight stile extensions on both sides, crossover platform, incl. back cage in accordance with DIN 18 799-1. In the case of other requirements, please use our planning system for fixed ladders.

Product features

Material	Warranty
Anodised aluminium	10 years



Product variants

SKU 58507	SKU 58518	SKU 58526
Overall length incl. stile 11.8 m	Overall length incl. stile 12.9 m	Overall length incl. stile 13.7 m
access height 10.7 m	access height 11.8 m	access height 12.6 m
SKU 58538	SKU 58549	SKU 58557
Overall length incl. stile 14.9 m	Overall length incl. stile 16 m	Overall length incl. stile 16.8 m
access height 13.8 m	access height 14.9 m	access height 15.7 m
SKU 58568	SKU 58580	SKU 58591
Overall length incl. stile 17.9 m	Overall length incl. stile 19.1 m	Overall length incl. stile 20.2 m
access height 16.8 m	access height 18 m	access height 19.1 m