



Hot-dip galvanised steel shaft ladder

Product description

- Internal ladder width: 300 mm.
- Rung spacing: 280 mm.
- Dimensions of stile: 50 x 20 mm.
- Dimensions of perforated rung: 29 x 29 mm.
- Material: hot-dip galvanised steel.



Hints and special features

A fall arrester device is mandatory in the case of possible falling heights in excess of 5.00 m. From an internal width of 300 mm upwards, it is attached to the stile. From an internal width of 400 mm upwards, it is attached in centred position on the rungs.
 assembly combination for further lengths on request.

Product features

Ladder width	Material	Pitch rung/tread	Tread depth	Warranty
340 mm	Steel, galvanised	280 mm	29 mm	10 years

Product variants

SKU	SKU	SKU
47321	47322	47323
Length	Length	Length
1.12 m	1.4 m	1.68 m
Number of rungs	Number of rungs	Number of rungs
4	5	6
Weight	Weight	Weight



5.2 kg	6.6 kg	8 kg
SKU 47324	SKU 47325	SKU 47326
Length 1.96 m	Length 2.24 m	Length 2.52 m
Number of rungs 7	Number of rungs 8	Number of rungs 9
Weight 9.4 kg	Weight 10.8 kg	Weight 12.2 kg
SKU 47327	SKU 47328	SKU 47329
Length 2.8 m	Length 3.08 m	Length 3.36 m
Number of rungs 10	Number of rungs 11	Number of rungs 12
Weight 13.6 kg	Weight 15 kg	Weight 16.4 kg
SKU 47623	SKU 47624	SKU 47625
Length 3.64 m	Length 3.92 m	Length 4.2 m
Number of rungs 13	Number of rungs 14	Number of rungs 15
Weight 17.8 kg	Weight 19.2 kg	Weight 20.6 kg