

Well cover, square, with ventilation chimney

Product description

- Lid made from sheet metal, 2.5 mm thick, elevated in the centre, with internal transverse bracing
- From 800 × 800 mm or Ø 800 mm with gas pressure springs.
- Self-locking fastener, locking mechanism can only be disengaged by hand.
- Frame prepared for setting in concrete and attachment with rawlplugs.
- EPDM seal on the underside of the lid




Product features

Shape


Square with ventilation chimney

Product variants


SKU 47110	SKU 47111	SKU 47112
Inside shaft length 625 mm	Inside shaft length 800 mm	Inside shaft length 1000 mm
Inside shaft size 625mm × 625mm	Inside shaft size 800mm × 800mm	Inside shaft size 1.000mm × 1.000mm
Inside shaft width 625 mm	Inside shaft width 800 mm	Inside shaft width 1000 mm
Material Steel, galvanised	Material Steel, galvanised	Material Steel, galvanised




Outside dimensions max. L x W x H 745 mm × 745 mm	Outside dimensions max. L x W x H 920 mm × 920 mm	Outside dimensions max. L x W x H 1.120 mm × 1.120 mm
Transport dimensions 740 mm × 740 mm × 460 mm	Transport dimensions 920 mm × 920 mm × 460 mm	Transport dimensions 1.120 mm × 1.120 mm × 460 mm
Version Without insulation	Version Without insulation	Version Without insulation
SKU 47118	SKU 47119	SKU 47120
Inside shaft length 625 mm	Inside shaft length 800 mm	Inside shaft length 1000 mm
Inside shaft size 625mm × 625mm	Inside shaft size 800mm × 800mm	Inside shaft size 1.000mm × 1.000mm
Inside shaft width 625 mm	Inside shaft width 800 mm	Inside shaft width 1000 mm
Material Steel, galvanised	Material Steel, galvanised	Material Galvanised steel
Outside dimensions max. L x W x H 745 mm × 745 mm	Outside dimensions max. L x W x H 920 mm × 920 mm	Outside dimensions max. L x W x H 1.120 mm × 1.120 mm
Transport dimensions 750 mm × 750 mm × 480 mm	Transport dimensions 920 mm × 920 mm × 480 mm	Transport dimensions 1.120 mm × 1.120 mm × 480 mm
Version With insulation	Version With insulation	Version With insulation
SKU 47114	SKU 47115	SKU 47180
Inside shaft length 625 mm	Inside shaft length 800 mm	Inside shaft length 1000 mm
Inside shaft size	Inside shaft size	Inside shaft size



625mm × 625mm	800mm × 800mm	1.000mm × 800mm
Inside shaft width 625 mm	Inside shaft width 800 mm	Inside shaft width 800 mm
Material Stainless steel	Material Stainless steel	Material Stainless steel
Outside dimensions max. L x W x H 745 mm × 745 mm	Outside dimensions max. L x W x H 920 mm × 920 mm	Outside dimensions max. L x W x H 1.120 mm × 920 mm
Transport dimensions 740 mm × 740 mm × 460 mm	Transport dimensions 920 mm × 920 mm × 460 mm	Transport dimensions 1.120 mm × 920 mm × 400 mm
Version Without insulation	Version Without insulation	Version Without insulation
SKU 47116	SKU 47117	SKU 47122
Inside shaft length 1000 mm	Inside shaft length 1200 mm	Inside shaft length 625 mm
Inside shaft size 1.000mm × 1.000mm	Inside shaft size 1.200mm × 1.200mm	Inside shaft size 625mm × 625mm
Inside shaft width 1000 mm	Inside shaft width 1200 mm	Inside shaft width 625 mm
Material Stainless steel	Material Stainless steel	Material Stainless steel
Outside dimensions max. L x W x H 1.120 mm × 1.120 mm	Outside dimensions max. L x W x H 1.320 mm × 1.320 mm	Outside dimensions max. L x W x H 745 mm × 745 mm
Transport dimensions 1.120 mm × 1.120 mm × 460 mm	Transport dimensions 1.320 mm × 1.320 mm × 460 mm	Transport dimensions 740 mm × 740 mm × 480 mm
Version Without insulation	Version Without insulation	Version With insulation



SKU 47123	SKU 47190	SKU 47124
Inside shaft length 800 mm	Inside shaft length 1000 mm	Inside shaft length 1000 mm
Inside shaft size 800mm × 800mm	Inside shaft size 1.000mm × 800mm	Inside shaft size 1.000mm × 1.000mm
Inside shaft width 800 mm	Inside shaft width 800 mm	Inside shaft width 1000 mm
Material Stainless steel	Material Stainless steel	Material Stainless steel
Outside dimensions max. L x W x H 920 mm × 920 mm	Outside dimensions max. L x W x H 1.120 mm × 920 mm	Outside dimensions max. L x W x H 1.120 mm × 1.120 mm
Transport dimensions 920 mm × 920 mm × 480 mm	Transport dimensions 1.120 mm × 920 mm × 460 mm	Transport dimensions 1.120 mm × 1.120 mm × 480 mm
Version With insulation	Version With insulation	Version With insulation
SKU 47125		
Inside shaft length 1200 mm		
Inside shaft size 1.200mm × 1.200mm		
Inside shaft width 1200 mm		
Material Stainless steel		
Outside dimensions max. L x W x H 1.320 mm × 1.320 mm		



Transport dimensions

1.320 mm × 1.320 mm × 480 mm

Version

With insulation