




Aluminium shaft covers with cover trough

Shaft covers that can be walked or driven on, with customisable inner and outer surface.

Product description


- Compliant with DIN EN 124 in conjunction with DIN 1229.
- Tapering section design, therefore easy to open. No sticking.
- Easy to open, no jamming.
- Odour-tight and impervious to surface water.
- Load with choice of surface: test force 125 kN (=12.5 t), only after cover trough has been filled by customer with B 45 concrete (grain 0-8).
- Incl. lift-out handles (pair) made from stainless steel, comprising one self-lifting opening handle and one lift-out handle.
- Trough depth 60 mm (of which 40 mm covered with construction steel grating and 20 mm free area)



Product features

Design height	Material, cover	Material, frame	Trough depth
80 mm	Aluminium	Aluminium	60 mm

Product variants





SKU	SKU	SKU
47000	47001	47002
Inside shaft length	Inside shaft length	Inside shaft length
300 mm	450 mm	500 mm
Inside shaft size	Inside shaft size	Inside shaft size
300mm × 300mm	450mm × 450mm	500mm × 500mm
Inside shaft width	Inside shaft width	Inside shaft width
300 mm	450 mm	500 mm
Outside dimensions max. L x W x H	Outside dimensions max. L x W x H	Outside dimensions max. L x W x H
440 mm × 440 mm	590 mm × 590 mm	640 mm × 640 mm
Transport dimensions	Transport dimensions	Transport dimensions
440 mm × 440 mm × 70 mm	590 mm × 590 mm × 70 mm	640 mm × 640 mm × 70 mm
SKU	SKU	SKU
47004	47005	47007
Inside shaft length	Inside shaft length	Inside shaft length
600 mm	635 mm	800 mm
Inside shaft size	Inside shaft size	Inside shaft size
600mm × 600mm	635mm × 635mm	800mm × 800mm
Inside shaft width	Inside shaft width	Inside shaft width
600 mm	635 mm	800 mm
Outside dimensions max. L x W x H	Outside dimensions max. L x W x H	Outside dimensions max. L x W x H
740 mm × 740 mm	775 mm × 775 mm	940 mm × 940 mm
Transport dimensions	Transport dimensions	Transport dimensions
740 mm × 740 mm × 70 mm	770 mm × 770 mm × 70 mm	940 mm × 940 mm × 70 mm
SKU		



47010

Inside shaft length

1000 mm

Inside shaft size

1.000mm × 1.000mm

Inside shaft width

1000 mm

Outside dimensions max. L x W x H

1.140 mm × 1.140 mm

Transport dimensions

1.140 mm × 1.140 mm × 70 mm