



Mobile access steps with platform

Mobile access or work platforms that offer comfortable ascent. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.

Product description

- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Individually adjustable platform lengths.
- Cantilever platform available for bridging obstacles.
- Chassis available in a non-static version as an option.
- Narrow chassis. The chassis width is reduced to a minimum through additional ballasting.
- Individual guardrail configuration on the platform, optionally with swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.



Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.



Standard applied: DIN EN ISO 14122.

Product features

Load capacity max. 300 kg	Max. load per tread 150 kg	Platform length 600 mm	Standards EN ISO 14122	Warranty 10 years
-------------------------------------	--------------------------------------	----------------------------------	----------------------------------	-----------------------------

Product variants

SKU 40255764	SKU 40255766	SKU 40255768
Chassis width 1020 mm	Chassis width 1620 mm	Chassis width 1620 mm
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 5	Number of treads 7	Number of treads 9
Overall span 1698 mm	Overall span 2128 mm	Overall span 2558 mm
Tread width 600 mm	Tread width 600 mm	Tread width 600 mm
Vertical height 1070 mm	Vertical height 1500 mm	Vertical height 1930 mm
SKU 40255770	SKU 40255772	SKU 40255774
Chassis width 1220 mm	Chassis width 1220 mm	Chassis width 1220 mm
Inclination 45 °	Inclination 45 °	Inclination 45 °



Number of treads 11	Number of treads 12	Number of treads 14
Overall span 3017 mm	Overall span 3447 mm	Overall span 3877 mm
Tread width 600 mm	Tread width 600 mm	Tread width 600 mm
Vertical height 2360 mm	Vertical height 2790 mm	Vertical height 3220 mm
SKU 40255776	SKU 40255778	SKU 40255780
Chassis width 1220 mm	Chassis width 1420 mm	Chassis width 1420 mm
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 16	Number of treads 18	Number of treads 20
Overall span 4307 mm	Overall span 4737 mm	Overall span 5167 mm
Tread width 600 mm	Tread width 600 mm	Tread width 600 mm
Vertical height 3650 mm	Vertical height 4080 mm	Vertical height 4510 mm
SKU 40255784	SKU 40255786	SKU 40255788
Chassis width 1020 mm	Chassis width 1220 mm	Chassis width 1220 mm
Inclination	Inclination	Inclination



45 °	45 °	45 °
Number of treads 5	Number of treads 7	Number of treads 9
Overall span 1698 mm	Overall span 2128 mm	Overall span 2558 mm
Tread width 800 mm	Tread width 800 mm	Tread width 800 mm
Vertical height 1070 mm	Vertical height 1500 mm	Vertical height 1930 mm
SKU 40255790	SKU 40255792	SKU 40255794
Chassis width 1220 mm	Chassis width 1220 mm	Chassis width 1420 mm
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 11	Number of treads 12	Number of treads 14
Overall span 3017 mm	Overall span 3447 mm	Overall span 3877 mm
Tread width 800 mm	Tread width 800 mm	Tread width 800 mm
Vertical height 2360 mm	Vertical height 2790 mm	Vertical height 3220 mm
SKU 40255796	SKU 40255798	SKU 40255800
Chassis width 1420 mm	Chassis width 1420 mm	Chassis width 1620 mm



Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 16	Number of treads 18	Number of treads 20
Overall span 4307 mm	Overall span 4737 mm	Overall span 5167 mm
Tread width 800 mm	Tread width 800 mm	Tread width 800 mm
Vertical height 3650 mm	Vertical height 4080 mm	Vertical height 4510 mm
SKU 40255804	SKU 40255806	SKU 40255808
Chassis width 1420 mm	Chassis width 1420 mm	Chassis width 1420 mm
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 5	Number of treads 7	Number of treads 9
Overall span 1698 mm	Overall span 2128 mm	Overall span 2558 mm
Tread width 1000 mm	Tread width 1000 mm	Tread width 1000 mm
Vertical height 1070 mm	Vertical height 1500 mm	Vertical height 1930 mm
SKU 40255810	SKU 40255812	SKU 40255814
Chassis width	Chassis width	Chassis width



1420 mm	1420 mm	1420 mm
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 11	Number of treads 12	Number of treads 14
Overall span 3017 mm	Overall span 3447 mm	Overall span 3877 mm
Tread width 1000 mm	Tread width 1000 mm	Tread width 1000 mm
Vertical height 2360 mm	Vertical height 2790 mm	Vertical height 3220 mm
SKU 40255816	SKU 40255818	SKU 40255820
Chassis width 1420 mm	Chassis width 1420 mm	Chassis width 1620 mm
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 16	Number of treads 18	Number of treads 20
Overall span 4307 mm	Overall span 4737 mm	Overall span 5167 mm
Tread width 1000 mm	Tread width 1000 mm	Tread width 1000 mm
Vertical height 3650 mm	Vertical height 4080 mm	Vertical height 4510 mm
SKU 40255704	SKU 40255706	SKU 40255708



Chassis width 1220 mm	Chassis width 1420 mm	Chassis width 1820 mm
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 5	Number of treads 7	Number of treads 9
Overall span 1453 mm	Overall span 1707 mm	Overall span 1996 mm
Tread width 600 mm	Tread width 600 mm	Tread width 600 mm
Vertical height 1250 mm	Vertical height 1750 mm	Vertical height 2250 mm
SKU 40255710	SKU 40255712	SKU 40255714
Chassis width 1620 mm	Chassis width 1620 mm	Chassis width 1620 mm
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 11	Number of treads 12	Number of treads 14
Overall span 2285 mm	Overall span 2607 mm	Overall span 2896 mm
Tread width 600 mm	Tread width 600 mm	Tread width 600 mm
Vertical height 2750 mm	Vertical height 3250 mm	Vertical height 3750 mm
SKU	SKU	SKU



40255716	40255724	40255726
Chassis width 1620 mm	Chassis width 1220 mm	Chassis width 1220 mm
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 17	Number of treads 5	Number of treads 7
Overall span 3185 mm	Overall span 1453 mm	Overall span 1707 mm
Tread width 600 mm	Tread width 800 mm	Tread width 800 mm
Vertical height 4250 mm	Vertical height 1250 mm	Vertical height 1750 mm
SKU 40255728	SKU 40255730	SKU 40255732
Chassis width 1620 mm	Chassis width 1420 mm	Chassis width 1420 mm
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 9	Number of treads 11	Number of treads 12
Overall span 1996 mm	Overall span 2285 mm	Overall span 2607 mm
Tread width 800 mm	Tread width 800 mm	Tread width 800 mm
Vertical height 2250 mm	Vertical height 2750 mm	Vertical height 3250 mm



SKU 40255734	SKU 40255736	SKU 40255744
Chassis width 1420 mm	Chassis width 1620 mm	Chassis width 1420 mm
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 14	Number of treads 17	Number of treads 5
Overall span 2896 mm	Overall span 3185 mm	Overall span 1453 mm
Tread width 800 mm	Tread width 800 mm	Tread width 1000 mm
Vertical height 3750 mm	Vertical height 4250 mm	Vertical height 1250 mm
SKU 40255746	SKU 40255748	SKU 40255750
Chassis width 1420 mm	Chassis width 1420 mm	Chassis width 1420 mm
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 7	Number of treads 9	Number of treads 11
Overall span 1707 mm	Overall span 1996 mm	Overall span 2285 mm
Tread width 1000 mm	Tread width 1000 mm	Tread width 1000 mm
Vertical height 1750 mm	Vertical height 2250 mm	Vertical height 2750 mm



SKU 40255752	SKU 40255754	SKU 40255756
Chassis width 1420 mm	Chassis width 1420 mm	Chassis width 1620 mm
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 12	Number of treads 14	Number of treads 17
Overall span 2607 mm	Overall span 2720 mm	Overall span 3207 mm
Tread width 1000 mm	Tread width 1000 mm	Tread width 1000 mm
Vertical height 3250 mm	Vertical height 3750 mm	Vertical height 4250 mm