



Mobile platform steps with ZARGES Ergo Stop

Mobile access or work platforms that offer comfortable ascent. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.



Product description

- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Individually adjustable platform lengths.
- Platform steps instantly ready for use due to an innovative brake system.
- Chassis available in a non-static version as an option.
- ZARGES Ergo Stop - all four castors can be braked conveniently using the footpedal on the flight of steps.
- Individual guardrail configuration on the platform, optionally with swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.

Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient



regulatory protection.

Standard applied: DIN EN ISO 14122.

Product features

Load capacity max. 300 kg	Max. load per tread 150 kg	Platform length 600 mm	Standards EN ISO 14122	Warranty 10 years
-------------------------------------	--------------------------------------	----------------------------------	----------------------------------	-----------------------------

Product variants

SKU 40255014	SKU 40255016	SKU 40255018
Chassis width 1020 mm	Chassis width 1620 mm	Chassis width 1620 mm
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 5	Number of treads 7	Number of treads 9
Overall span 1698 mm	Overall span 2128 mm	Overall span 2558 mm
Tread width 600 mm	Tread width 600 mm	Tread width 600 mm
Vertical height 1070 mm	Vertical height 1500 mm	Vertical height 1930 mm
SKU 40255020	SKU 40255022	SKU 40255024
Chassis width 1220 mm	Chassis width 1220 mm	Chassis width 1220 mm
Inclination	Inclination	Inclination



45 °	45 °	45 °
Number of treads 11	Number of treads 12	Number of treads 14
Overall span 3017 mm	Overall span 3447 mm	Overall span 3877 mm
Tread width 600 mm	Tread width 600 mm	Tread width 600 mm
Vertical height 2360 mm	Vertical height 2790 mm	Vertical height 3220 mm
SKU 40255026	SKU 40255028	SKU 40255030
Chassis width 1220 mm	Chassis width 1420 mm	Chassis width 1420 mm
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 16	Number of treads 18	Number of treads 20
Overall span 4307 mm	Overall span 4737 mm	Overall span 5167 mm
Tread width 600 mm	Tread width 600 mm	Tread width 600 mm
Vertical height 3650 mm	Vertical height 4080 mm	Vertical height 4510 mm
SKU 40255034	SKU 40255036	SKU 40255038
Chassis width 1020 mm	Chassis width 1220 mm	Chassis width 1220 mm



Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 5	Number of treads 7	Number of treads 9
Overall span 1698 mm	Overall span 2128 mm	Overall span 2558 mm
Tread width 800 mm	Tread width 800 mm	Tread width 800 mm
Vertical height 1070 mm	Vertical height 1500 mm	Vertical height 1930 mm
SKU 40255040	SKU 40255042	SKU 40255044
Chassis width 1220 mm	Chassis width 1220 mm	Chassis width 1420 mm
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 11	Number of treads 12	Number of treads 14
Overall span 3017 mm	Overall span 3447 mm	Overall span 3877 mm
Tread width 800 mm	Tread width 800 mm	Tread width 800 mm
Vertical height 2360 mm	Vertical height 2790 mm	Vertical height 3220 mm
SKU 40255046	SKU 40255048	SKU 40255050
Chassis width	Chassis width	Chassis width



1420 mm	1420 mm	1620 mm
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 16	Number of treads 18	Number of treads 20
Overall span 4307 mm	Overall span 4737 mm	Overall span 5167 mm
Tread width 800 mm	Tread width 800 mm	Tread width 800 mm
Vertical height 3650 mm	Vertical height 4080 mm	Vertical height 4510 mm
SKU 40255054	SKU 40255056	SKU 40255058
Chassis width 1420 mm	Chassis width 1420 mm	Chassis width 1420 mm
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 5	Number of treads 7	Number of treads 9
Overall span 1698 mm	Overall span 2128 mm	Overall span 2558 mm
Tread width 1000 mm	Tread width 1000 mm	Tread width 1000 mm
Vertical height 1070 mm	Vertical height 1500 mm	Vertical height 1930 mm
SKU 40255060	SKU 40255062	SKU 40255064



Chassis width 1420 mm	Chassis width 1420 mm	Chassis width 1420 mm
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 11	Number of treads 12	Number of treads 14
Overall span 3017 mm	Overall span 3447 mm	Overall span 3877 mm
Tread width 1000 mm	Tread width 1000 mm	Tread width 1000 mm
Vertical height 2360 mm	Vertical height 2790 mm	Vertical height 3220 mm
SKU 40255066	SKU 40255068	SKU 40255070
Chassis width 1420 mm	Chassis width 1420 mm	Chassis width 1620 mm
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 16	Number of treads 18	Number of treads 20
Overall span 4307 mm	Overall span 4737 mm	Overall span 5167 mm
Tread width 1000 mm	Tread width 1000 mm	Tread width 1000 mm
Vertical height 3650 mm	Vertical height 4080 mm	Vertical height 4510 mm
SKU	SKU	SKU



40255074	40255076	40255078
Chassis width 1220 mm	Chassis width 1420 mm	Chassis width 1820 mm
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 5	Number of treads 7	Number of treads 9
Overall span 1453 mm	Overall span 1707 mm	Overall span 1996 mm
Tread width 600 mm	Tread width 600 mm	Tread width 600 mm
Vertical height 1250 mm	Vertical height 1750 mm	Vertical height 2250 mm
SKU 40255080	SKU 40255082	SKU 40255084
Chassis width 1620 mm	Chassis width 1620 mm	Chassis width 1620 mm
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 11	Number of treads 13	Number of treads 15
Overall span 2285 mm	Overall span 2607 mm	Overall span 2896 mm
Tread width 600 mm	Tread width 600 mm	Tread width 600 mm
Vertical height 2750 mm	Vertical height 3250 mm	Vertical height 3750 mm



SKU 40255086	SKU 40255094	SKU 40255096
Chassis width 1620 mm	Chassis width 1220 mm	Chassis width 1220 mm
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 17	Number of treads 5	Number of treads 7
Overall span 3185 mm	Overall span 1453 mm	Overall span 1707 mm
Tread width 600 mm	Tread width 800 mm	Tread width 800 mm
Vertical height 4250 mm	Vertical height 1250 mm	Vertical height 1750 mm
SKU 40255098	SKU 40255100	SKU 40255102
Chassis width 1620 mm	Chassis width 1420 mm	Chassis width 1420 mm
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 9	Number of treads 11	Number of treads 12
Overall span 1996 mm	Overall span 2285 mm	Overall span 2607 mm
Tread width 800 mm	Tread width 800 mm	Tread width 800 mm
Vertical height 2250 mm	Vertical height 2750 mm	Vertical height 3250 mm



SKU 40255104	SKU 40255106	SKU 40255114
Chassis width 1420 mm	Chassis width 1620 mm	Chassis width 1420 mm
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 15	Number of treads 17	Number of treads 5
Overall span 2896 mm	Overall span 3185 mm	Overall span 1453 mm
Tread width 800 mm	Tread width 800 mm	Tread width 1000 mm
Vertical height 3750 mm	Vertical height 4250 mm	Vertical height 1250 mm
SKU 40255116	SKU 40255118	SKU 40255120
Chassis width 1420 mm	Chassis width 1420 mm	Chassis width 1420 mm
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 7	Number of treads 9	Number of treads 11
Overall span 1707 mm	Overall span 1820 mm	Overall span 2285 mm
Tread width 1000 mm	Tread width 1000 mm	Tread width 1000 mm
Vertical height	Vertical height	Vertical height



1750 mm	2250 mm	2750 mm
SKU 40255122	SKU 40255124	SKU 40255126
Chassis width 1420 mm	Chassis width 1620 mm	Chassis width 1620 mm
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 13	Number of treads 14	Number of treads 17
Overall span 2607 mm	Overall span 3009 mm	Overall span 3298 mm
Tread width 1000 mm	Tread width 1000 mm	Tread width 1000 mm
Vertical height 3250 mm	Vertical height 3750 mm	Vertical height 4250 mm