



Access steps

Stationary access to buildings and machines.

Product description

- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Stiles made from high-strength aluminium extrusions with screw channels for flexible assembly options.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.
- Hook-on cantilevers, set of hooks and support bracket to integrate the product as detachable in a fixing.
- Plastic support plate for floor bracket for fast removal of product.
- Standard applied: DIN EN ISO 14122.



Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14122.

Product features





Load capacity max. 300 kg	Max. load per tread 150 kg	Standards EN ISO 14122	Warranty 10 years
-------------------------------------	--------------------------------------	----------------------------------	-----------------------------

Product variants

SKU 40055244	SKU 40055246	SKU 40055248
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 5	Number of treads 7	Number of treads 9
Overall span 1117 mm	Overall span 1547 mm	Overall span 1977 mm
Tread width 600 mm	Tread width 600 mm	Tread width 600 mm
Vertical height 1070 mm	Vertical height 1500 mm	Vertical height 1930 mm
SKU 40055250	SKU 40055252	SKU 40055254
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 11	Number of treads 13	Number of treads 15
Overall span 2435 mm	Overall span 2865 mm	Overall span 3295 mm
Tread width 600 mm	Tread width 600 mm	Tread width 600 mm
Vertical height	Vertical height	Vertical height



2360 mm	2790 mm	3220 mm
SKU 40055256	SKU 40055258	SKU 40055264
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 17	Number of treads 19	Number of treads 5
Overall span 3725 mm	Overall span 4155 mm	Overall span 1117 mm
Tread width 600 mm	Tread width 600 mm	Tread width 800 mm
Vertical height 3650 mm	Vertical height 4080 mm	Vertical height 1070 mm
SKU 40055266	SKU 40055268	SKU 40055270
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 7	Number of treads 9	Number of treads 11
Overall span 1547 mm	Overall span 1977 mm	Overall span 2435 mm
Tread width 800 mm	Tread width 800 mm	Tread width 800 mm
Vertical height 1500 mm	Vertical height 1930 mm	Vertical height 2360 mm
SKU 40055272	SKU 40055274	SKU 40055276



Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 13	Number of treads 15	Number of treads 17
Overall span 2865 mm	Overall span 3295 mm	Overall span 3725 mm
Tread width 800 mm	Tread width 800 mm	Tread width 800 mm
Vertical height 2790 mm	Vertical height 3220 mm	Vertical height 3650 mm
SKU 40055278	SKU 40055344	SKU 40055346
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 19	Number of treads 5	Number of treads 7
Overall span 4155 mm	Overall span 1117 mm	Overall span 1547 mm
Tread width 800 mm	Tread width 1000 mm	Tread width 1000 mm
Vertical height 4080 mm	Vertical height 1070 mm	Vertical height 1500 mm
SKU 40055348	SKU 40055350	SKU 40055352
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads	Number of treads	Number of treads



9	11	13
Overall span 1977 mm	Overall span 2435 mm	Overall span 2865 mm
Tread width 1000 mm	Tread width 1000 mm	Tread width 1000 mm
Vertical height 1930 mm	Vertical height 2360 mm	Vertical height 2790 mm
SKU 40055354	SKU 40055356	SKU 40055358
Inclination 45 °	Inclination 45 °	Inclination 45 °
Number of treads 15	Number of treads 17	Number of treads 19
Overall span 3295 mm	Overall span 3725 mm	Overall span 4155 mm
Tread width 1000 mm	Tread width 1000 mm	Tread width 1000 mm
Vertical height 3220 mm	Vertical height 3650 mm	Vertical height 4080 mm
SKU 40055204	SKU 40055206	SKU 40055208
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 5	Number of treads 7	Number of treads 9
Overall span 793 mm	Overall span 1081 mm	Overall span 1370 mm



Tread width 600 mm	Tread width 600 mm	Tread width 600 mm
Vertical height 1250 mm	Vertical height 1750 mm	Vertical height 2250 mm
SKU 40055210	SKU 40055212	SKU 40055214
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 11	Number of treads 13	Number of treads 15
Overall span 1659 mm	Overall span 1947 mm	Overall span 2304 mm
Tread width 600 mm	Tread width 600 mm	Tread width 600 mm
Vertical height 2750 mm	Vertical height 3250 mm	Vertical height 3750 mm
SKU 40055216	SKU 40055218	SKU 40055224
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 17	Number of treads 19	Number of treads 5
Overall span 2593 mm	Overall span 2881 mm	Overall span 793 mm
Tread width 600 mm	Tread width 600 mm	Tread width 800 mm
Vertical height	Vertical height	Vertical height



4250 mm	4750 mm	1250 mm
SKU 40055226	SKU 40055228	SKU 40055230
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 7	Number of treads 9	Number of treads 11
Overall span 1081 mm	Overall span 1370 mm	Overall span 1659 mm
Tread width 800 mm	Tread width 800 mm	Tread width 800 mm
Vertical height 1750 mm	Vertical height 2250 mm	Vertical height 2750 mm
SKU 40055232	SKU 40055234	SKU 40055236
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 13	Number of treads 15	Number of treads 17
Overall span 1947 mm	Overall span 2304 mm	Overall span 2593 mm
Tread width 800 mm	Tread width 800 mm	Tread width 800 mm
Vertical height 3250 mm	Vertical height 3750 mm	Vertical height 4250 mm
SKU 40055238	SKU 40055324	SKU 40055326



Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 19	Number of treads 5	Number of treads 7
Overall span 2881 mm	Overall span 793 mm	Overall span 1081 mm
Tread width 800 mm	Tread width 1000 mm	Tread width 1000 mm
Vertical height 4750 mm	Vertical height 1250 mm	Vertical height 1750 mm
SKU 40055328	SKU 40055330	SKU 40055332
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads 9	Number of treads 11	Number of treads 13
Overall span 1370 mm	Overall span 1659 mm	Overall span 1947 mm
Tread width 1000 mm	Tread width 1000 mm	Tread width 1000 mm
Vertical height 2250 mm	Vertical height 2750 mm	Vertical height 3250 mm
SKU 40055334	SKU 40055336	SKU 40055338
Inclination 60 °	Inclination 60 °	Inclination 60 °
Number of treads	Number of treads	Number of treads



15	17	19
Overall span 2304 mm	Overall span 2593 mm	Overall span 2881 mm
Tread width 1000 mm	Tread width 1000 mm	Tread width 1000 mm
Vertical height 3750 mm	Vertical height 4250 mm	Vertical height 4750 mm