



R13step S

Safer ascent with the highest non-slip performance thanks to R13 treads for oily and wet environment.

Product description

- Safer ascent with the highest non-slip performance thanks to R13 treads for oily and wet environment.
- Large platform with R13 surface that allows personnel to stand safely and comfortably even when working for extended periods.
- Practical tray with plenty of space for tools and small items.
- 80 mm deep treads with R13 surface and perforations to drain fast.
- Abrasion-resistant, anodised stiles.
- Practical aluminium storage tray for small items and tools.
- Platform made from extruded aluminium (300 mm × 250 mm) with R13 surface for safer and comfortable standing even when working for longer periods of time.
- High-strength Perlon belts prevent splay, fitted on all models of 5 rungs or more.
- Maximum working heights thanks to 280mm high access.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.





Hints and special features

Platform and treads with R13 surface.

Complies with EN 131 Professional.

Product features

Coating anodised	Connection Stile-Rung flanged	Load capacity max. 150 kg	Material Aluminium	Pitch rung/tread 265 mm
Platform length 250 mm	Platform width 300 mm	Standards EN 131 professional	Stile depth 73 mm	Stile depth 58 mm
Stile depth steps/back stay 73mm / 58mm	Tray Aluminium	Tread depth 80 mm	Type rung/tread R13 tread	Warranty 10 years

Product variants

SKU 41636	SKU 41637	SKU 41638
Base 0,57 m × 0,5 m	Base 0,76 m × 0,53 m	Anti splay Belt strap
Number of rungs, incl. platform 3	Number of rungs, incl. platform 4	Base 0,96 m × 0,56 m
Overall base width 0.5 m	Overall base width 0.53 m	Number of rungs, incl. platform 5
Overall length 1.59 m	Overall length 1.87 m	Overall base width 0.56 m



Platform height 0.8 m	Platform height 1.06 m	Overall length 2.15 m
Transport dimensions approx. 1.590 mm × approx. 500 mm × approx. 170 mm	Transport dimensions approx. 1.870 mm × approx. 530 mm × approx. 170 mm	Platform height 1.33 m
Weight 8.3 kg	Weight 9.8 kg	Transport dimensions approx. 2.150 mm × approx. 560 mm × approx. 170 mm
Working height 2.8 m	Working height 3.1 m	Weight 10.5 kg
		Working height 3.35 m
SKU 41639	SKU 41640	SKU 41641
Anti splay Belt strap	Anti splay Belt strap	Anti splay Belt strap
Base 1,15 m × 0,59 m	Base 1,34 m × 0,62 m	Base 1,53 m × 0,65 m
Number of rungs, incl. platform 6	Number of rungs, incl. platform 7	Number of rungs, incl. platform 8
Overall base width 0.59 m	Overall base width 0.62 m	Overall base width 0.65 m
Overall length 2.43 m	Overall length 2.71 m	Overall length 2.99 m
Platform height 1.59 m	Platform height 1.85 m	Platform height 2.12 m



Transport dimensions approx. 2.430 mm × approx. 590 mm × approx. 170 mm	Transport dimensions approx. 2.710 mm × approx. 620 mm × approx. 170 mm	Transport dimensions approx. 2.990 mm × approx. 650 mm × approx. 170 mm
Weight 11.5 kg	Weight 12.3 kg	Weight 12.8 kg
Working height 3.6 m	Working height 3.85 m	Working height 4.15 m
SKU 41642		
Anti splay Belt strap		
Base 1,91 m × 0,71 m		
Number of rungs, incl. platform 10		
Overall base width 0.71 m		
Overall length 3.55 m		
Platform height 2.64 m		
Transport dimensions approx. 3.550 mm × approx. 710 mm × approx. 170 mm		
Weight 16.1 kg		



Working height

4.65 m