



R13step B

The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.

Product description

- The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.
- 80 mm deep treads with R13 surface and perforations to drain fast.
- Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Maximum working heights thanks to 280mm high access.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay Belt strap	Coating anodised	Connection Stile-Rung flanged	Load capacity max. 150 kg	Material Aluminium
Pitch rung/tread 265 mm	Standards EN 131 professional	Stile depth 73 mm	Tread depth 80 mm	Type rung/tread R13 tread
Warranty 10 years				

Product variants



SKU 41549	SKU 41551	SKU 41553
Base 0,79 m × 0,44 m	Base 0,98 m × 0,47 m	Base 1,18 m × 0,5 m
Number of treads 2 × 3	Number of treads 2 × 4	Number of treads 2 × 5
Overall base width 0.44 m	Overall base width 0.47 m	Overall base width 0.5 m
Overall length 0.88 m	Overall length 1.15 m	Overall length 1.42 m
Transport dimensions approx. 880 mm × approx. 450 mm × approx. 220 mm	Transport dimensions approx. 1.155 mm × approx. 475 mm × approx. 220 mm	Transport dimensions approx. 1.440 mm × approx. 500 mm × approx. 220 mm
Vertical ladder height 0.8 m	Vertical ladder height 1.06 m	Vertical ladder height 1.32 m
Weight 5.8 kg	Weight 7.2 kg	Weight 8.4 kg
Working height 2.3 m	Working height 2.55 m	Working height 2.8 m
SKU 41555	SKU 41557	SKU 41559
Base 1,37 m × 0,53 m	Base 1,57 m × 0,56 m	Base 1,77 m × 0,59 m
Number of treads 2 × 6	Number of treads 2 × 7	Number of treads 2 × 8
Overall base width 0.53 m	Overall base width 0.56 m	Overall base width 0.59 m
Overall length	Overall length	Overall length



1.7 m	1.98 m	2.27 m
Transport dimensions approx. 1.750 mm × approx. 530 mm × approx. 220 mm	Transport dimensions approx. 2.000 mm × approx. 560 mm × approx. 220 mm	Transport dimensions approx. 2.280 mm × approx. 590 mm × approx. 220 mm
Vertical ladder height 1.58 m	Vertical ladder height 1.84 m	Vertical ladder height 2.1 m
Weight 9.3 kg	Weight 10.1 kg	Weight 11.5 kg
Working height 3.05 m	Working height 3.3 m	Working height 3.6 m
SKU 41561	SKU 41563	SKU 41565
Base 2,16 m × 0,65 m	Base 2,55 m × 0,71 m	Base 2,95 m × 0,77 m
Number of treads 2 × 10	Number of treads 2 × 12	Number of treads 2 × 14
Overall base width 0.65 m	Overall base width 0.71 m	Overall base width 0.77 m
Overall length 2.83 m	Overall length 3.39 m	Overall length 3.95 m
Transport dimensions approx. 2.840 mm × approx. 650 mm × approx. 220 mm	Transport dimensions approx. 3.390 mm × approx. 710 mm × approx. 220 mm	Transport dimensions approx. 3.950 mm × approx. 770 mm × approx. 220 mm
Vertical ladder height 2.62 m	Vertical ladder height 3.15 m	Vertical ladder height 3.67 m
Weight 14.7 kg	Weight 17.8 kg	Weight 22.6 kg
Working height 4.15 m	Working height 4.65 m	Working height 5.2 m



SKU		
41567		
Base		
3,34 m × 0,83 m		
Number of treads		
2 × 16		
Overall base width		
0.83 m		
Overall length		
4.51 m		
Transport dimensions		
approx. 4.510 mm × approx. 830 mm × approx. 220 mm		
Vertical ladder height		
4.21 m		
Weight		
26.6 kg		
Working height		
5.7 m		