



# Armex

Practical features and robust design for daily maintenance work.

## Product description

- In the area of work positioning, breathable shoulder, hip and leg padding that does not cut into you, and the wide waist belt ensure that you can work comfortably all day long. Robust material loops also facilitate perfect workplace organisation so that the necessary tools are within easy reach. Armex robust and comfortable full body harness in accordance with EN 361:2002 for work positioning in accordance with EN 358:2018, with numerous features for maximum safety. These include the innovations Chair in the Air, NFC tag, WebAlert and automatic belt buckles.
- Automatic belt buckles and numerous adjustment options for fast application and an optimal fit.
- Chair In The Air - the unique solution against suspension trauma. Directly integrated into the harness. Even inexperienced persons can safely position themselves after a fall in just 5 seconds.
- Webalert - warns about cracked belts.
- ZmartCheck - provides quick access to security-relevant information.
- Aluminium eyelets sternal, dorsal and ventral - light and robust.
- Use a ventral aluminium fall arrester eye in accordance with EN 361 in conjunction with EN 353-1
- Folding side attachment elements (lateral) do not impede climbing.
- Breathable, wide back and hip pads, leg pads and shoulder straps are removable - for maximum comfort.
- Robust material loops (20 kg load capacity) and a lanyard park ensure safe workplace organisation.
- Suitable for people up to 150 kg.





- A fall indicator is located on the lower back of the dorsal attachment point. If the load exceeds 6 kN, a label becomes visible: WARNING. Fall indicator.
- Label field on the product label bag.

## Hints and special features

Complies with EN 361.

## Product features

Automatic Buckles <b>Yes</b>	Chair in the Air <b>Yes</b>	Fall Indicator <b>Yes</b>	Lanyard Parking <b>Yes</b>	Material Buckles <b>Steel</b>
Material Dorsal Attachment Point <b>Aluminium</b>	Material Sternal Attachment Point <b>Aluminium</b>	Material Webbing <b>Polyester</b>	Maximum Service Life <b>10 J</b>	Maximum Weight of User <b>150 kg</b>
NFC-Tag <b>Yes</b>	Padding <b>Missing translation</b>	Smart Check <b>Yes</b>	Web Alert <b>Yes</b>	

## Product variants

SKU <b>47804</b>	SKU <b>47805</b>	SKU <b>47870</b>
Attachement Points <b>Sternal attachment pointDorsal attachment pointDorsal attachment point</b>	Attachement Points <b>Sternal attachment pointDorsal attachment pointDorsal attachment point</b>	Attachement Points <b>Sternal attachment pointDorsal attachment pointDorsal attachment point</b>
Size <b>S-M</b>	Size <b>L-XXL</b>	Size <b>3XL</b>
Standards <b>EN 361EN 358</b>	Standards <b>EN 361EN 358</b>	Standards <b>EN 361EN 358</b>
Weight <b>2.25 kg</b>	Weight <b>2.3 kg</b>	Weight <b>2.35 kg</b>

