



AXIC-Y

Double lanyard with elastic arms according to EN 354:2010 and integrated energy absorber according to EN 355:2002. The integrated O-ring prevents the arms from twisting during use. The length is flexible and can be varied between 1.40 m and 1.80 m. The lanyard is optionally equipped with carabiners or rebar hooks.

Product description

- Double lanyard according to EN 354:2010 with energy absorber according to EN 355:2002.
- Flexible length between 1.40 and 1.80 m.
- Equipped with carabiners or rebar hooks.
- Due to its round shape, the central RING eyelet allows optimal positioning to prevent twisting.
- Suitable for people up to 150 kg.
- ZmartCheck - provides quick access to security-relevant information.
- Suitable for sharp edges, RfU 11.074.
- DIN 19427



Product features

Length Range	Maximum Service Life	Maximum length	Minimum length
1,4-1,8 m	10 J	1.8 m	1.4 m

Product variants

SKU 47809	SKU 47860	SKU 47863
Anchoring Carabiner Aluminum rebar hook	Anchoring Carabiner Aluminum rebar hook	Anchoring Carabiner Aluminum rebar hook
Harness Carabiner Aluminum snap carabiner	Energy Absorber Yes	Energy Absorber Yes



Standards EN 354EN 355	Harness Carabiner Twist-lock	Harness Carabiner Tri-lock
Weight 1.8 kg	Smart Check Yes	Smart Check Yes
	Standards EN 354EN 355	Standards EN 354EN 355
	Weight 1.85 kg	Weight 1.85 kg
SKU 47810	SKU 47861	SKU 47864
Anchoring Carabiner Aluminum snap carabiner	Anchoring Carabiner Aluminum snap carabiner	Anchoring Carabiner Aluminum snap carabiner
Harness Carabiner Aluminum snap carabiner	Energy Absorber Yes	Energy Absorber Yes
Standards EN 354EN 355	Harness Carabiner Twist-lock	Harness Carabiner Tri-lock
Weight 1.1 kg	Smart Check Yes	Smart Check Yes
	Standards EN 354EN 355	Standards EN 354EN 355
	Weight 1.15 kg	Weight 1.15 kg
SKU 47867		
Anchoring Carabiner Maxi Rebar hook		
Energy Absorber		



Yes

Harness Carabiner

Aluminum snap carabiner

Smart Check

Yes

Standards

EN 354EN 355

Weight

1.9 kg