ZARGES

DATA SHEET

# K 470 universal case, IP 65 - 366212

TÜV Süd-certified box with pressure equalization valve—ideal for all applications requiring enhanced protection against moisture, water spray, and dust.




## PRODUCT DESCRIPTION

- TÜV Süd-certified box with pressure equalization valve—ideal for all applications requiring enhanced protection against moisture, water spray, and dust.
- IP 65 protection rating in accordance with DIN EN 60529, achieved by a foamed gasket integrated into the cover.
- 22 standard sizes of the K 470 are available from stock in IP65. The three variants with lengths of 1,400 mm or more also offer enhanced protection thanks to an optimized seal and pressure-equalizing valve, but do not fully meet the requirements of protection class IP65.
- Also available with approval for the transportation of hazardous goods.
- Extra thick 1.5-mm sheet metal for all K 470 containers from basic dimensions of 750 x 550 mm.
- Automatic pressure-equalizing diaphragm.
- TÜV SÜD-certified.
- Available for most K 470 models.







### HINTS AND SPECIAL FEATURES

UN approval for the transportation of hazardous goods possible at additional charge.
Clearance measurement approx. 30mm (1.2") less than internal dimension (length and width). Special sizes on request.

## PRODUCT FEATURES

| Property | Value |
|---|---|
| Certification | TÜV Süd - IP 65 |

| Property | Value |
| --- | --- |
| Colour of the stacking corners | Natural aluminium |
| Corner beading | Yes |
| Fasteners | Comfort fasteners |
| Handles | Sprung drop handles |
| Integrated wheels | No |
| Internal dimensions L x W x H | 600 mm × 560 mm × 440 mm |
| Material | Aluminium |
| Material of the stacking corners | Aluminium |
| Max. gross weight dangerous goods permission | 83 kg |
| Number of handles | 2 |
| Outside dimensions max. L x W x H | 650 mm × 610 mm × 470 mm |
| Peripheral beading | Yes |
| Protection class | IP65: |
| Seal | foamed lid seal |
| Stacking corners | Yes |
| Volume | 148 l |
| Warranty | 10 years |
| Weight | 7.4 kg |

**ZARGES GMBH**
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/8/2026
Subject to change or error.