

K 470 universal case, IP 65

- 366217

For all applications where extra leak-tightness and greater protection against moisture, water jets and dust is required.

Product description

- For all applications where extra leak-tightness and greater protection against moisture, water jets and dust is required.
- Protection class IP 65 in accordance with EN 60 529 through foamed seal in the lid.
- 3 standard sizes ex stock, customised versions available on request.
- Also available with approval for the transportation of hazardous goods.
- Extra thick 1.5-mm sheet metal for all K 470 containers from basic dimensions of 750 x 550 mm.
- Automatic pressure compensation membrane
- Leak-tightness verified with TÜV SÜD certificate.
- Available for most K 470 models.



Hints and special features

UN approval for the transportation of hazardous goods possible at additional charge.

Clearance measurement approx. 30mm (1.2") less than internal dimension (length and width). Special sizes on request.

Product features



Colour of the stacking corners	Natural aluminium
Corner beading	Yes
Fasteners	Comfort fasteners
Integrated wheels	No
Internal dimensions L x W x H	750 mm x 550 mm x 380 mm
Material	Aluminium
Material of the stacking corners	Aluminium
Max. gross weight dangerous goods permission	102 kg
Number of handles	2
Outside dimensions max. L x W x H	800 mm x 600 mm x 410 mm
Peripheral beading	Yes
Protection class	IP65:
Seal	foamed lid seal
Stacking corners	Yes
Volume	157 l
Warranty	10 years
Weight	10 kg
certification-mark-pf	TÜV Süd - IP 65

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 3/27/2026

Subject to change or error.