

# Fuelling ladder with 6 treads - 40051

The universal platform ladder for all kinds of demanding applications. You can also use this ladder as a refuelling ladder to help you get work done quickly and safely.

## Product description

- The universal platform ladder for all kinds of demanding applications. You can also use this ladder as a refuelling ladder to help you get work done quickly and safely.
- Our ladder is equipped with two removable mounts for securely holding underwing refuelling nozzles on the ladder's access section.
- A stabiliser on the ladder's support section ensures safe standing. Also available in other widths.
- The spacious platform (500x450mm) made of steel grating ensures maximum secure footing thanks to its R13 slip-resistance rating and design that allows liquids to drain off.
- Two wheels on the access section ensure easy ladder operation. The wheels can also be attached to the support section.
- Increased safety even with oily substances or ice during outdoor applications.
- Large, serrated-surface standing platform for safe and comfortable working.
- Easily collapsible for transport and storage.



- 80 mm deep treads with R13 surface and perforations to drain fast.
- All-round railings.
- Wide horizontal stabiliser bar.

## Product features

Anti splay <b>Belt strap</b>	Coating <b>natural</b>	Connection Stile-Rung <b>flanged</b>	Load capacity <b>max. 150 kg</b>	Material <b>Natural aluminium</b>
Number of rungs, incl. platform <b>6</b>	Overall base width <b>1400 mm</b>	Pitch rung/tread <b>265 mm</b>	Platform height <b>1.6 m</b>	Platform length <b>500 mm</b>
Platform width <b>450 mm</b>	Standards <b>EN 131-7</b>	Stile depth <b>73 mm</b>	Transport dimensions <b>2.550 mm × 1.450 mm × 400 mm</b>	Tread depth <b>80 mm</b>
Type rung/tread <b>R13 tread</b>	Warranty <b>10 years</b>	Weight <b>20 kg</b>	Wide crosspiece <b>1.4 m</b>	Working height <b>3.6 m</b>
non-static <b>Yes</b>				