ZARGES

DATA SHEET

# Access steps - 40055230

Stationary access to buildings and machines.





## PRODUCT DESCRIPTION

- Stationary access to buildings and machines.
- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Treads and platform surfaces are made of grooved aluminum (R10) as standard.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Stiles made from high-strength aluminium extrusions with screw channels for flexible assembly options.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.
- Hook-on cantilevers, set of hooks and support bracket to integrate the product as detachable in a fixing.
- Plastic support plate for floor bracket for fast removal of product.
- Standard applied: DIN EN ISO 14?122.

## HINTS AND SPECIAL FEATURES

Standard applied: DIN EN ISO 14?122.

## PRODUCT FEATURES

| Property | Value |
|---|---|
| Inclination | 60 ° |
| Load capacity | max. 300 kg |
| Max. load per tread | 150 kg |

| Property | Value |
| --- | --- |
| Number of treads | 11 |
| Overall span | 1659 mm |
| Standards | NF EN ISO 14122-4 |
| Tread width | 800 mm |
| Vertical height | 2750 mm |
| Warranty | 10 years |

## ACCESSORIES AND SPARE PARTS

### ACCESSORIES 1



**Handrail, 11 steps**
SKU 42355290

### SPARE PARTS 1

**clamping lever**
SKU 800512

**ZARGES GMBH**
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 10/31/2026
Subject to change or error.