

Access steps - 40055234

Stationary access to buildings and machines.

Product description

- Stationary access to buildings and machines.
- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Stiles made from high-strength aluminium extrusions with screw channels for flexible assembly options.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.
- Hook-on cantilevers, set of hooks and support bracket to integrate the product as detachable in a fixing.
- Plastic support plate for floor bracket for fast removal of product.
- Standard applied: DIN EN ISO 14112.



Hints and special features

Standard applied: DIN EN ISO 14112.



Product features

| | |
|---------------------|-------------------|
| Inclination | 60 ° |
| Load capacity | max. 300 kg |
| Max. load per tread | 150 kg |
| Number of treads | 15 |
| Overall span | 2304 mm |
| Standards | NF EN ISO 14122-4 |
| Tread width | 800 mm |
| Vertical height | 3750 mm |
| Warranty | 10 years |

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/3/2026

Subject to change or error.