ZARGES

DATA SHEET

Access steps - 40055332

Stationary access to buildings and machines.





PRODUCT DESCRIPTION

- Stationary access to buildings and machines.
- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Treads and platform surfaces are made of grooved aluminum (R10) as standard.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Stiles made from high-strength aluminium extrusions with screw channels for flexible assembly options.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.
- Hook-on cantilevers, set of hooks and support bracket to integrate the product as detachable in a fixing.
- Plastic support plate for floor bracket for fast removal of product.
- Standard applied: DIN EN ISO 14?122.

HINTS AND SPECIAL FEATURES

Standard applied: DIN EN ISO 14?122.

PRODUCT FEATURES

Property	Value
Inclination	60 °
Load capacity	max. 300 kg
Max. load per tread	150 kg

Property	Value
Number of treads	13
Overall span	1947 mm
Standards	NF EN ISO 14122-4
Tread width	1000 mm
Vertical height	3250 mm
Warranty	10 years

ACCESSORIES AND SPARE PARTS

ACCESSORIES 1



Handrail, 13 steps
SKU 42355292

SPARE PARTS 1

clamping lever
SKU 800512

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 10/31/2026
Subject to change or error.