

## Access steps - 40055356

Stationary access to buildings and machines.

### Product description

- Stationary access to buildings and machines.
- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Treads and platform surfaces are made of grooved aluminum (R10) as standard.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Stiles made from high-strength aluminium extrusions with screw channels for flexible assembly options.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.
- Hook-on cantilevers, set of hooks and support bracket to integrate the product as detachable in a fixing.
- Plastic support plate for floor bracket for fast removal of product.
- Standard applied: DIN EN ISO 14122.



### Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall

protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14122.

## Product features

Inclination	45 °
Load capacity	max. 300 kg
Max. load per tread	150 kg
Number of treads	17
Overall span	3725 mm
Standards	NF EN ISO 14122-4
Tread width	1000 mm
Vertical height	3650 mm
Warranty	10 years

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 6/17/2026

Subject to change or error.