

## Fuelling ladder with 5 treads - 40099

The universal platform ladder for any heavy-duty application! Or specifically as a refuelling ladder.

### Product description

- The universal platform ladder for any heavy-duty application! Or specifically as a refuelling ladder.
- Our ladder is equipped with two removable mounts for securely holding underwing refuelling nozzles on the ladder's access section.
- The crossbar on the ladder's support section ensures stability.
- The spacious platform (450 x 500 mm), made of steel grating with a slip resistance rating of R13, ensures maximum stability.
- Two electrically conductive rollers on the riser provide a simple method for moving the conductors.
- Increased safety even with oily substances or ice during outdoor applications.
- Large, serrated-surface standing platform for safe and comfortable working.
- Easily collapsible for transport and storage.
- 80 mm deep treads with R13 tread and grooves, as well as perforations to allow liquids to drain, for noticeably better traction in any situation.
- All-round railings.
- Wide horizontal stabiliser bar.





## Product features

|                                 |                              |
|---------------------------------|------------------------------|
| Anti splay                      | Belt strap                   |
| Coating                         | natural                      |
| Connection Stile-Rung           | flanged                      |
| Load capacity                   | max. 150 kg                  |
| Material                        | Natural aluminium            |
| Number of rungs, incl. platform | 5                            |
| Overall base width              | 1200 mm                      |
| Pitch rung/tread                | 265 mm                       |
| Platform height                 | 1.35 m                       |
| Platform length                 | 500 mm                       |
| Platform width                  | 450 mm                       |
| Standards                       | EN 131-7                     |
| Stile depth                     | 73 mm                        |
| Transport dimensions            | 2.350 mm × 1.250 mm × 400 mm |
| Tread depth                     | 80 mm                        |
| Type rung/tread                 | R13 tread                    |
| Warranty                        | 10 years                     |
| Weight                          | 18 kg                        |
| Wide crosspiece                 | 1.2 m                        |
| Working height                  | 3.35 m                       |
| non-static                      | Yes                          |



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

[zarges@zarges.de](mailto:zarges@zarges.de)

[www.zarges.com](http://www.zarges.com)

Effective 6/30/2026

Subject to change or error.