

Fuelling ladder with 5 treads - 40099

The universal platform ladder for any heavy-duty application! Or specifically as a refuelling ladder.

Product description

- The universal platform ladder for any heavy-duty application! Or specifically as a refuelling ladder.
- Our ladder is equipped with two removable mounts for securely holding underwing refuelling nozzles on the ladder's access section.
- The crossbar on the ladder's support section ensures stability.
- The spacious platform (450 x 500 mm), made of steel grating with a slip resistance rating of R13, ensures maximum stability.
- Two electrically conductive rollers on the riser provide a simple method for moving the conductors.
- Increased safety even with oily substances or ice during outdoor applications.
- Large, serrated-surface standing platform for safe and comfortable working.
- Easily collapsible for transport and storage.
- 80 mm deep treads with R13 tread and grooves, as well as perforations to allow liquids to drain, for noticeably better traction in any situation.
- All-round railings.
- Wide horizontal stabiliser bar.





Product features

Anti splay	Belt strap
Coating	natural
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Natural aluminium
Number of rungs, incl. platform	5
Overall base width	1200 mm
Pitch rung/tread	265 mm
Platform height	1.35 m
Platform length	500 mm
Platform width	450 mm
Standards	EN 131-7
Stile depth	73 mm
Transport dimensions	2.350 mm × 1.250 mm × 400 mm
Tread depth	80 mm
Type rung/tread	R13 tread
Warranty	10 years
Weight	18 kg
Wide crosspiece	1.2 m
Working height	3.35 m
non-static	Yes



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/16/2026

Subject to change or error.