DATA SHEET

RCstep BP - 40139

PRODUCT DESCRIPTION

- Treads and platform with a unique texture for maximum slip resistance (R13).
- Platform size approx. 600 x 300 mm.
- Optimal stability thanks to a rigid connection on both sides with pressure reinforcement.
- Extra-deep treads (92 mm) for comfortable and safe standing.
- Double-sided access.
- Clean hands thanks to wear-resistant anodised stiles.
- New design - high-quality 2-component plastic ladder shoe - also suitable for working on gratings.





HINTS AND SPECIAL FEATURES

Complies with EN 14183, VNA 205/2009, and AFS 2023:9.

PRODUCT FEATURES

Property	Value
Base	0,99 m × 0,96 m
Certification	TÜV-SÜD
Coating	anodised
Connection Stile-Rung	riveted
Load capacity	150 kg

Property	Value
Material	Anodised aluminium
Number of treads	4
Number of treads	2 × 4
Overall base width	0.96 m
Pitch rung/tread	250 mm
Platform height	0.99 m
Platform length	300 mm
Platform width	600 mm
Standards	EN 14183,AFS 2023:9,VNA205/2009
Stile depth	48 mm
Transport dimensions	approx. 1.105 mm × approx. 960 mm × approx. 290 mm
Tread depth	92 mm
Type rung/tread	RC tread
Warranty	10 years
Weight	9.3 kg
Working height	2.99 m

ACCESSORIES AND SPARE PARTS

SPARE PARTS 3



Push-on end cap
SKU 21012290



Spreader without lock, left
SKU 800475



Spreader without lock, right
SKU 800476

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/15/2026
Subject to change or error.