



# Access steps with platform

## - 40155364

Stationary access to buildings and machines with platforms.

### Product description

- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Individually adjustable platform lengths.
- Support section mounting element for use as a free-standing work platform.
- Individual guardrail configuration on the platform, optionally with swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Stiles made from high-strength aluminium extrusions with screw channels for flexible assembly options.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.



### Hints and special features



We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Configure your individual steps at

[www.zargesconfigurator.com](http://www.zargesconfigurator.com) Can't find the solution you need? Contact our specialist consultants! We have solutions even for complex requirements! Tel.: +49 881 687 -101

Standard applied: DIN EN ISO 14122.

## Product features

|                                  |                                       |                                      |                                   |                                |
|----------------------------------|---------------------------------------|--------------------------------------|-----------------------------------|--------------------------------|
| Inclination<br><b>60 °</b>       | Load capacity<br><b>max. 300 kg</b>   | Max. load per tread<br><b>150 kg</b> | Number of treads<br><b>5</b>      | Overall span<br><b>1407 mm</b> |
| Platform length<br><b>600 mm</b> | Standards<br><b>NF EN ISO 14122-4</b> | Tread width<br><b>600 mm</b>         | Vertical height<br><b>1250 mm</b> | Warranty<br><b>10 years</b>    |