

# Skyline 2E - 40207

Easy and convenient vertical height adjustment makes this ladder ideal for use to access very great heights.

## Product description

- Easy and convenient vertical height adjustment makes this ladder ideal for use to access very great heights.
- Very easy and convenient rung-by-rung height adjustment in a 280 mm grid via synthetic rope and roller.
- Locks securely thanks to automatic spring loaded pawls.
- Top ladder section fitted with wall wheels.
- Wheel assemblies with abrasion-resistant surfaces that will not damage the wall.
- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.




## Hints and special features

Convenient rung-by-rung height adjustment, with wall wheels that will not damage the wall.

Complies with EN 131 Professional.

## Product features



Coating <b>natural</b>	Connection Stile-Rung <b>flanged</b>	External width of lower ladder <b>490 mm</b>	Load capacity <b>max. 150 kg</b>	Material <b>Aluminium</b>
Number of rungs <b>16</b>	Number of rungs <b>2 × 16</b>	Overall length, extended <b>8.33 m</b>	Overall length, retracted <b>4.7 m</b>	Pitch rung/tread <b>270 mm</b>
Standards <b>EN 131 professional</b>	Stile depth <b>98 mm</b>	Stile depth <b>98mm</b>	Transport dimensions <b>approx. 4.670 mm × approx. 520 mm × approx. 200 mm</b>	Tread depth <b>30 mm</b>
Type rung/tread <b>serrated</b>	Warranty <b>10 years</b>	Weight <b>25.9 kg</b>	Wheels <b>Rubber</b>	Wide crosspiece <b>1.2 m</b>
Working height <b>9 m</b>	certification-mark-pf <b>TÜV-SÜD</b>			