

## Skyline 2E - 40208

Easy and convenient vertical height adjustment makes this ladder ideal for use to access very great heights.

### Product description

- Easy and convenient vertical height adjustment makes this ladder ideal for use to access very great heights.
- Very easy and convenient rung-by-rung height adjustment in a 280 mm grid via synthetic rope and roller.
- Locks securely thanks to automatic spring loaded pawls.
- Top ladder section fitted with wall wheels.
- Wheel assemblies with abrasion-resistant surfaces that will not damage the wall.
- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



### Hints and special features

Convenient rung-by-rung height adjustment, with wall wheels that will not damage the wall.

Complies with EN 131 Professional.

### Product features

Certification	TÜV-SÜD
Coating	natural



Connection Stile-Rung	flanged
External width of lower ladder	490 mm
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	18
Number of rungs	2 × 18
Overall length, extended	9.13 m
Overall length, retracted	5.2 m
Pitch rung/tread	270 mm
Standards	EN 131 professional
Stile depth	98 mm
Stile depth	98mm
Transport dimensions	approx. 5.200 mm × approx. 520 mm × approx. 200 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years
Weight	32.2 kg
Wheels	Rubber
Wide crosspiece	1.2 m
Working height	9.75 m



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

[zarges@zarges.de](mailto:zarges@zarges.de)

[www.zarges.com](http://www.zarges.com)

Effective 6/26/2026

Subject to change or error.