

## Everest 2E - 40217

The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.

### Product description

- The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.
- From length of 8.30 m – upper ladder with wheel assemblies. Wall wheels with wear-resistant surfaces that will not damage the wall.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 40245-40247
- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- Plastic anti-friction insert and lift-off retainer.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Coating	Connection Stile-Rung	External width of lower ladder	Load capacity	Material
---------	-----------------------	--------------------------------	---------------	----------

natural	flanged	490 mm	max. 150 kg	Aluminium
Number of rungs <b>24</b>	Number of rungs <b>2 × 24</b>	Overall length, extended <b>12.22 m</b>	Overall length, retracted <b>6.9 m</b>	Pitch rung/tread <b>270 mm</b>
Standards <b>EN 131 professional</b>	Stile depth <b>114 mm</b>	Transport dimensions <b>6.900 mm × 500 mm × 230 mm</b>	Tread depth <b>30 mm</b>	Type rung/tread <b>serrated</b>
Warranty <b>10 years</b>	Weight <b>41.5 kg</b>	Wheels <b>Rubber</b>	Wide crosspiece <b>1.2 m</b>	Working height <b>12.75 m</b>
certification-mark-pf <b>TÜV-SÜD</b>				