

Everest 2E - 40217

The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.

Product description

- The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.
- From length of 8.30 m – upper ladder with wheel assemblies. Wall wheels with wear-resistant surfaces that will not damage the wall.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 40245-40247
- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- Plastic anti-friction insert and lift-off retainer.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Certification	TÜV-SÜD
Coating	natural



Connection Stile-Rung	flanged
External width of lower ladder	490 mm
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	24
Number of rungs	2 × 24
Overall length, extended	12.22 m
Overall length, retracted	6.9 m
Pitch rung/tread	270 mm
Standards	EN 131 professional
Stile depth	114 mm
Transport dimensions	6.900 mm × 500 mm × 230 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years
Weight	41.5 kg
Wheels	Rubber
Wide crosspiece	1.2 m
Working height	12.75 m

ZARGES GmbH

Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/29/2026

Subject to change or error.