

## Everest 2E - 40247

The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.

### Product description

- The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.
- From length of 8.30 m – upper ladder with wheel assemblies. Wall wheels with wear-resistant surfaces that will not damage the wall.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 40245-40247
- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- Both parts of the ladder can also be used separately as single ladders.
- Plastic anti-friction insert and lift-off retainer.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Certification	TÜV-SÜD
---------------	---------



Coating	natural
Connection Stile-Rung	flanged
External width of lower ladder	490 mm
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	10
Number of rungs	2 × 10
Overall length, extended	4.96 m
Overall length, retracted	3 m
Pitch rung/tread	270 mm
Standards	EN 131 professional
Stile depth	68 mm
Transport dimensions	3.000 mm × 500 mm × 140 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years
Weight	13.5 kg
Wheels	Rubber
Wide crosspiece	1 m
Working height	5.75 m



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

[zarges@zarges.de](mailto:zarges@zarges.de)

[www.zarges.com](http://www.zarges.com)

Effective 5/14/2026

Subject to change or error.