

Everest 2E - 40249

The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.

Product description

- The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.
- From length of 8.30 m – upper ladder with wheel assemblies. Wall wheels with wear-resistant surfaces that will not damage the wall.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos.

40245-40247

- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- Plastic anti-friction insert and lift-off retainer.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating	Connection Stile-Rung	External width of lower ladder	Load capacity	Material



natural	flanged	490 mm	max. 150 kg	Aluminium
Number of rungs 14	Number of rungs 2 × 14	Overall length, extended 7.21 m	Overall length, retracted 4.07 m	Pitch rung/tread 270 mm
Standards EN 131 professional	Stile depth 85 mm	Transport dimensions 4.130 mm × 500 mm × 160 mm	Tread depth 30 mm	Type rung/tread serrated
Warranty 10 years	Weight 19.5 kg	Wheels Rubber	Wide crosspiece 1.2 m	Working height 7.9 m
certification-mark-pf TÜV-SÜD				