

# Mobile platform steps with ZARGES Ergo Stop - 40255096



Mobile access or work platforms that offer comfortable ascent. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.

## Product description

- Mobile access or work platforms that offer comfortable ascent. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.
- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Individually adjustable platform lengths.
- Platform steps instantly ready for use due to an innovative brake system.
- Chassis available in a non-static version as an option.
- ZARGES Ergo Stop - all four castors can be braked conveniently using the footpedal on the flight of

steps.

- Individual guardrail configuration on the platform, optionally with swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.

## Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14122.

## Product features

Chassis width	1220 mm
Inclination	60 °
Load capacity	max. 300 kg
Max. load per tread	150 kg
Number of treads	7
Overall span	1707 mm
Platform length	600 mm
Standards	NF EN ISO 14122-4



Tread width	800 mm
Vertical height	1750 mm
Warranty	10 years

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 5/2/2026

Subject to change or error.