

Coni B - 40274

Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.



Product description

- Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.
- Sturdy aluminium alloy rungs (30 x 30 mm) with non-slip serrated surface.
- Sturdy, solidly screwed steel hinges
- Two high-strength Perlon belts, secured without twisting to the rung, prevent splay.
- High strength, non-twist rung/stile connections.
- Additional stabilisation by bracing on the bottom rung.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Stepladder for maximum working heights of up to 6.70 m.

Complies with EN 131 Professional.

Product features

| Anti splay | Base | Coating | Connection Stile-Rung | Load capacity |
|------------|------|---------|-----------------------|---------------|
|------------|------|---------|-----------------------|---------------|



| | | | | |
|-----------------------|----------------------------|-----------------|-----------------------------------|--------------------|
| Belt strap | 0,78 m x 0,48 m | natural | flanged | max. 150 kg |
| Material | Number of rungs | Number of rungs | Overall base width | Overall length |
| Aluminium | 4 | 2 x 4 | 0.48 m | 1.25 m |
| Pitch rung/tread | Standards | Stile depth | Transport dimensions | Tread depth |
| 265 mm | EN 131 professional | 50 mm | 1.250 mm x 480 mm x 170 mm | 30 mm |
| Type rung/tread | Vertical ladder height | Warranty | Weight | Working height |
| serrated | 1.2 m | 10 years | 4.4 kg | 2.5 m |
| certification-mark-pf | | | | |
| TÜV-SÜD | | | | |