

## Coni B - 40274

Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.

### Product description

- Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.
- Sturdy aluminium alloy rungs (30 x 30 mm) with non-slip serrated surface.
- Sturdy, solidly screwed steel hinges
- Two high-strength Perlon belts, secured without twisting to the rung, prevent splay.
- High strength, non-twist rung/stile connections.
- Additional stabilisation by bracing on the bottom rung.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



### Hints and special features

Stepladder for maximum working heights of up to 6.70 m.

Complies with EN 131 Professional.

### Product features

Anti splay	Base	Coating	Connection Stile-Rung	Load capacity
------------	------	---------	-----------------------	---------------

Belt strap	0,78 m × 0,48 m	natural	flanged	max. 150 kg
Material <b>Aluminium</b>	Number of rungs <b>4</b>	Number of rungs <b>2 × 4</b>	Overall base width <b>0.48 m</b>	Overall length <b>1.25 m</b>
Pitch rung/tread <b>265 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>50 mm</b>	Transport dimensions <b>1.250 mm × 480 mm × 170 mm</b>	Tread depth <b>30 mm</b>
Type rung/tread <b>serrated</b>	Vertical ladder height <b>1.2 m</b>	Warranty <b>10 years</b>	Weight <b>4.4 kg</b>	Working height <b>2.5 m</b>