

Coni B - 40275

Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.

Product description

- Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.
- Sturdy aluminium alloy rungs (30 x 30 mm) with non-slip serrated surface.
- Sturdy, solidly screwed steel hinges
- Two high-strength Perlon belts, secured without twisting to the rung, prevent splay.
- High strength, non-twist rung/stile connections.
- Additional stabilisation by bracing on the bottom rung.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Stepladder for maximum working heights of up to 6.70 m.

Complies with EN 131 Professional.

Product features

Anti splay	Base	Coating	Connection Stile-Rung	Load capacity
------------	------	---------	-----------------------	---------------

Belt strap	0,93 m × 0,51 m	natural	flanged	max. 150 kg
Material Aluminium	Number of rungs 5	Number of rungs 2 × 5	Overall base width 0.51 m	Overall length 1.53 m
Pitch rung/tread 265 mm	Standards EN 131 professional	Stile depth 58 mm	Transport dimensions 1.530 mm × 510 mm × 170 mm	Tread depth 30 mm
Type rung/tread serrated	Vertical ladder height 1.46 m	Warranty 10 years	Weight 5.8 kg	Working height 2.75 m