

Coni B - 40311

Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.

Product description

- Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.
- Sturdy aluminium alloy rungs (30 x 30 mm) with non-slip serrated surface.
- Sturdy, solidly screwed steel hinges
- Anti-spread protection provided by two high-strength polyester webbing straps, securely attached to the rungs to prevent twisting.
- High strength, non-twist rung/stile connections.
- Additional stabilisation by bracing on the bottom rung.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Stepladder for maximum working heights of up to 6.70 m.

Complies with EN 131 Professional.

Product features

Anti splay	Belt strap
Base	1,07 m × 0,54 m



Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	6
Number of rungs	2 × 6
Overall base width	0.54 m
Overall length	1.81 m
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	58 mm
Transport dimensions	1.810 mm × approx. 540 mm × approx. 170 mm
Tread depth	30 mm
Type rung/tread	serrated
Vertical ladder height	1.73 m
Warranty	10 years
Weight	6.8 kg
Working height	3 m

ZARGES GmbH

Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/28/2026

Subject to change or error.