



Coni B - 40313

Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.

Product description

- Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.
- Sturdy aluminium alloy rungs (30 x 30 mm) with non-slip serrated surface.
- Sturdy, solidly screwed steel hinges
- Two high-strength Perlon belts, secured without twisting to the rung, prevent splay.
- High strength, non-twist rung/stile connections.
- Additional stabilisation by bracing on the bottom rung.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Stepladder for maximum working heights of up to 6.70 m.

Complies with EN 131 Professional.

Product features

Anti splay	Base	Coating	Connection Stile-Rung	Load capacity
------------	------	---------	-----------------------	---------------



Belt strap	1,65 m x 0,66 m	natural	flanged	max. 150 kg
Material	Number of rungs	Number of rungs	Overall base width	Overall length
Aluminium	10	2 x 10	0.66 m	2.92 m
Pitch rung/tread	Standards	Stile depth	Transport dimensions	Tread depth
265 mm	EN 131 professional	58 mm	approx. 2.930 mm x approx. 660 mm x approx. 170 mm	30 mm
Type rung/tread	Vertical ladder height	Warranty	Weight	Working height
serrated	2.83 m	10 years	11.1 kg	4.05 m
certification-mark-pf TÜV-SÜD				