

## Coni B - 40313

Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.

### Product description

- Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.
- Sturdy aluminium alloy rungs (30 x 30 mm) with non-slip serrated surface.
- Sturdy, solidly screwed steel hinges
- Anti-spread protection provided by two high-strength polyester webbing straps, securely attached to the rungs to prevent twisting.
- High strength, non-twist rung/stile connections.
- Additional stabilisation by bracing on the bottom rung.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



### Hints and special features

Stepladder for maximum working heights of up to 6.70 m.

Complies with EN 131 Professional.

### Product features

Anti splay	Belt strap
Base	1,65 m × 0,66 m



Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	10
Number of rungs	2 × 10
Overall base width	0.66 m
Overall length	2.92 m
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	58 mm
Transport dimensions	approx. 2.930 mm × approx. 660 mm × approx. 170 mm
Tread depth	30 mm
Type rung/tread	serrated
Vertical ladder height	2.83 m
Warranty	10 years
Weight	11.1 kg
Working height	4.05 m

ZARGES GmbH

Zargesstraße 7  
82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

[zarges@zarges.de](mailto:zarges@zarges.de)

[www.zarges.com](http://www.zarges.com)

Effective 6/28/2026

Subject to change or error.