



## Coni B - 40320

Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.

### Product description

- Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.
- Sturdy aluminium alloy rungs (30 x 30 mm) with non-slip serrated surface.
- Sturdy, solidly screwed steel hinges
- Two high-strength Perlon belts, secured without twisting to the rung, prevent splay.
- High strength, non-twist rung/stile connections.
- Additional stabilisation by bracing on the bottom rung.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



### Hints and special features

Stepladder for maximum working heights of up to 6.70 m.

Complies with EN 131 Professional.

### Product features

Anti splay	Base	Coating	Connection Stile-Rung	Load capacity
------------	------	---------	-----------------------	---------------



<b>Belt strap</b>	<b>2,84 m × 0,9 m</b>	<b>natural</b>	<b>flanged</b>	<b>max. 150 kg</b>
Material	Number of rungs	Number of rungs	Overall base width	Overall length
<b>Aluminium</b>	<b>18</b>	<b>2 × 18</b>	<b>0.9 m</b>	<b>5.17 m</b>
Pitch rung/tread	Standards	Stile depth	Transport dimensions	Tread depth
<b>265 mm</b>	<b>EN 131 professional</b>	<b>73 mm</b>	<b>approx. 5.170 mm × approx. 900 mm × approx. 200 mm</b>	<b>30 mm</b>
Type rung/tread	Vertical ladder height	Warranty	Weight	Working height
<b>serrated</b>	<b>5 m</b>	<b>10 years</b>	<b>25.6 kg</b>	<b>6.15 m</b>
certification-mark-pf <b>TÜV-SÜD</b>				