

Seventec S - 40334

High stability, comfortable ascent and descent due to deep treads and smooth external stile surfaces that are comfortable to grip.

Product description

- High stability, comfortable ascent and descent due to deep treads and smooth external stile surfaces that are comfortable to grip.
- Comfortable standing on a large platform with integrated hinge connection.
- Treads 85 mm deep for safe standing.
- Large safety platform (380 x 260 mm) with integrated hinged connection.
- Optimal stability thanks to the fold-down locking bar on both sides.
- Practical tray with plenty of space for tools and small items.
- Two integrated bucket hooks.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Smooth external stile surfaces that are comfortable to hold.
- Treads and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay Rigid locking bar	Base 0,88 m × 0,47 m	Coating natural	Connection Stile-Rung riveted	Load capacity max. 150 kg
Material Aluminium	Number of rungs, incl. platform 4	Overall base width 0.47 m	Overall length 1.67 m	Pitch rung/tread 218 mm
Platform height 0.9 m	Platform length 260 mm	Platform width 380 mm	Standards EN 131 professional	Stile depth 87 mm
Stile depth 87 mm	Stile depth steps/back stay 87mm / 87mm	Transport dimensions 1.680 mm × 490 mm × 250 mm	Tray Aluminium	Tread depth 85 mm
Type rung/tread serrated	Vertical ladder height 1.54 m	Warranty 10 years	Weight 7 kg	Working height 2.9 m