

Seventec S - 40338

High stability, comfortable ascent and descent due to deep treads and smooth external stile surfaces that are comfortable to grip.

Product description

- High stability, comfortable ascent and descent due to deep treads and smooth external stile surfaces that are comfortable to grip.
- Comfortable standing on a large platform with integrated hinge connection.
- Treads 85 mm deep for safe standing.
- Large safety platform (380 x 260 mm) with integrated hinged connection.
- Optimal stability thanks to the fold-down locking bar on both sides.
- Practical tray with plenty of space for tools and small items.
- Two integrated bucket hooks.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Smooth external stile surfaces that are comfortable to hold.
- Treads and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.

Product features



Anti splay	Rigid locking bar
Base	1,51 m × 0,56 m
Coating	natural
Connection Stile-Rung	riveted
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs, incl. platform	8
Overall base width	0.56 m
Overall length	2.6 m
Pitch rung/tread	218 mm
Platform height	1.75 m
Platform length	260 mm
Platform width	380 mm
Standards	EN 131 professional
Stile depth	87 mm
Stile depth	87 mm
Stile depth steps/back stay	87mm / 87mm
Transport dimensions	2.590 mm × 570 mm × 250 mm
Tray	Aluminium
Tread depth	85 mm
Type rung/tread	serrated
Vertical ladder height	2.41 m



Warranty	10 years
Weight	13 kg
Working height	3.75 m
certification-mark-pf	TÜV-SÜD

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 3/29/2026

Subject to change or error.