

## Seventec S - 40340

High stability, comfortable ascent and descent due to deep treads and smooth external stile surfaces that are comfortable to grip.

### Product description

- High stability, comfortable ascent and descent due to deep treads and smooth external stile surfaces that are comfortable to grip.
- Comfortable standing on a large platform with integrated hinge connection.
- Treads 85 mm deep for safe standing.
- Large safety platform (380 x 260 mm) with integrated hinged connection.
- Optimal stability thanks to the fold-down locking bar on both sides.
- Practical tray with plenty of space for tools and small items.
- Two integrated bucket hooks.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Smooth external stile surfaces that are comfortable to hold.
- Treads and stiles made from extruded aluminium sections.



### Hints and special features

Complies with EN 131 Professional.

### Product features



Anti splay	Base	Coating	Connection Stile-Rung	Load capacity
<b>Rigid locking bar</b>	<b>1,82 m × 0,6 m</b>	<b>natural</b>	<b>riveted</b>	<b>max. 150 kg</b>
Material	Number of rungs, incl. platform	Overall base width	Overall length	Pitch rung/tread
<b>Aluminium</b>	<b>10</b>	<b>0.61 m</b>	<b>3.05 m</b>	<b>218 mm</b>
Platform height	Platform length	Platform width	Standards	Stile depth
<b>2.2 m</b>	<b>260 mm</b>	<b>380 mm</b>	<b>EN 131 professional</b>	<b>87 mm</b>
Stile depth	Stile depth steps/back stay	Transport dimensions	Tray	Tread depth
<b>87 mm</b>	<b>87mm / 87mm</b>	<b>3.050 mm × 630 mm × 250 mm</b>	<b>Aluminium</b>	<b>85 mm</b>
Type rung/tread	Vertical ladder height	Warranty	Weight	Working height
<b>serrated</b>	<b>2.82 m</b>	<b>10 years</b>	<b>14 kg</b>	<b>4.2 m</b>
certification-mark-pf				
<b>TÜV-SÜD</b>				